



**Pressure Type Wire
Connector Combinations
Budget Terminals and Splices
(Use Type “F” Tooling)**

408-2049-28
14 OCT 11 Rev.D

CU

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

WIRE SIZE RANGE (AWG) AND TYPE

	424C LISTED
22-16 Solid or Stranded	22-16 Stranded
16-14 Solid or Stranded	16-14 Stranded
12-10 Stranded	12-10 Stranded

Note: Terminals and splices used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928 (formerly MIL-T-7928).

DANGER: Not to be used on aluminum wire; otherwise, may cause equipment failure leading to serious injury or death.

©2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company
All Rights Reserved
TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.
TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
For Regional Customer Service, visit our website at www.te.com

LOC B



**Pressure Type Wire
Connector Combinations
Budget Terminals and Splices
(Use Type “F” Tooling)**

408-2049-28
14 OCT 11 Rev.D

CU

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

WIRE SIZE RANGE (AWG) AND TYPE

	424C LISTED
22-16 Solid or Stranded	22-16 Stranded
16-14 Solid or Stranded	16-14 Stranded
12-10 Stranded	12-10 Stranded

Note: Terminals and splices used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928 (formerly MIL-T-7928).

DANGER: Not to be used on aluminum wire; otherwise, may cause equipment failure leading to serious injury or death.

©2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company
All Rights Reserved
TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.
TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
For Regional Customer Service, visit our website at www.te.com

LOC B



**Pressure Type Wire
Connector Combinations
Budget Terminals and Splices
(Use Type “F” Tooling)**

408-2049-28
14 OCT 11 Rev.D

CU

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

WIRE SIZE RANGE (AWG) AND TYPE

	424C LISTED
22-16 Solid or Stranded	22-16 Stranded
16-14 Solid or Stranded	16-14 Stranded
12-10 Stranded	12-10 Stranded

Note: Terminals and splices used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928 (formerly MIL-T-7928).

DANGER: Not to be used on aluminum wire; otherwise, may cause equipment failure leading to serious injury or death.

©2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company
All Rights Reserved
TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.
TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
For Regional Customer Service, visit our website at www.te.com

LOC B



**Pressure Type Wire
Connector Combinations
Budget Terminals and Splices
(Use Type “F” Tooling)**

408-2049-28
14 OCT 11 Rev.D

CU

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

WIRE SIZE RANGE (AWG) AND TYPE

	424C LISTED
22-16 Solid or Stranded	22-16 Stranded
16-14 Solid or Stranded	16-14 Stranded
12-10 Stranded	12-10 Stranded

Note: Terminals and splices used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928 (formerly MIL-T-7928).

DANGER: Not to be used on aluminum wire; otherwise, may cause equipment failure leading to serious injury or death.

©2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company
All Rights Reserved
TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.
TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
For Regional Customer Service, visit our website at www.te.com

LOC B



**Pressure Type Wire
Connector Combinations
Budget Terminals and Splices
(Use Type “F” Tooling)**

408-2049-28
14 OCT 11 Rev.D

CU

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

WIRE SIZE RANGE (AWG) AND TYPE

	424C LISTED
22-16 Solid or Stranded	22-16 Stranded
16-14 Solid or Stranded	16-14 Stranded
12-10 Stranded	12-10 Stranded

Note: Terminals and splices used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928 (formerly MIL-T-7928).

DANGER: Not to be used on aluminum wire; otherwise, may cause equipment failure leading to serious injury or death.

©2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company
All Rights Reserved
TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.
TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
For Regional Customer Service, visit our website at www.te.com

LOC B



**Pressure Type Wire
Connector Combinations
Budget Terminals and Splices
(Use Type “F” Tooling)**

408-2049-28
14 OCT 11 Rev.D

CU

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

WIRE SIZE RANGE (AWG) AND TYPE

	424C LISTED
22-16 Solid or Stranded	22-16 Stranded
16-14 Solid or Stranded	16-14 Stranded
12-10 Stranded	12-10 Stranded

Note: Terminals and splices used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928 (formerly MIL-T-7928).

DANGER: Not to be used on aluminum wire; otherwise, may cause equipment failure leading to serious injury or death.

©2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company
All Rights Reserved
TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.
TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
For Regional Customer Service, visit our website at www.te.com

LOC B



**Pressure Type Wire
Connector Combinations
Budget Terminals and Splices
(Use Type “F” Tooling)**

408-2049-28
14 OCT 11 Rev.D

CU

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

WIRE SIZE RANGE (AWG) AND TYPE

	424C LISTED
22-16 Solid or Stranded	22-16 Stranded
16-14 Solid or Stranded	16-14 Stranded
12-10 Stranded	12-10 Stranded

Note: Terminals and splices used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928 (formerly MIL-T-7928).

DANGER: Not to be used on aluminum wire; otherwise, may cause equipment failure leading to serious injury or death.

©2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company
All Rights Reserved
TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.
TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
For Regional Customer Service, visit our website at www.te.com

LOC B