



408-2049-29
29 OCT 14 Rev F
CU

**PLASTI-GRIP* Pressure Type
Straight and 90-Degree Bent
Terminals (Use Tooling for
AMPLI-BOND* Connectors)**

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

600 Volts Max

105 °C [222 °F] Max

UL and CSA Wire Combinations



Recognized Under the
Component Program of
UL File E13288



LR 7189
CERTIFIED

8-2/0 AWG
Stranded Wire

8-2/0 AWG
Solid or Stranded Wire

Note: Only certain terminal part numbers apply.

©2014 TE Connectivity family of companies
All Rights Reserved
*Trademark

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752

For latest revision and Regional Customer Service,
visit our website at www.te.com

TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks. Other logos, product and/or company names may be trademarks of their respective owners.



408-2049-29
29 OCT 14 Rev F
CU

**PLASTI-GRIP* Pressure Type
Straight and 90-Degree Bent
Terminals (Use Tooling for
AMPLI-BOND* Connectors)**

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

600 Volts Max

105 °C [222 °F] Max

UL and CSA Wire Combinations



Recognized Under the
Component Program of
UL File E13288



LR 7189
CERTIFIED

8-2/0 AWG
Stranded Wire

8-2/0 AWG
Solid or Stranded Wire

Note: Only certain terminal part numbers apply.

©2014 TE Connectivity family of companies
All Rights Reserved
*Trademark

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752

For latest revision and Regional Customer Service,
visit our website at www.te.com

TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks. Other logos, product and/or company names may be trademarks of their respective owners.



408-2049-29
29 OCT 14 Rev F
CU

**PLASTI-GRIP* Pressure Type
Straight and 90-Degree Bent
Terminals (Use Tooling for
AMPLI-BOND* Connectors)**

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

600 Volts Max

105 °C [222 °F] Max

UL and CSA Wire Combinations



Recognized Under the
Component Program of
UL File E13288



LR 7189
CERTIFIED

8-2/0 AWG
Stranded Wire

8-2/0 AWG
Solid or Stranded Wire

Note: Only certain terminal part numbers apply.

©2014 TE Connectivity family of companies
All Rights Reserved
*Trademark

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752

For latest revision and Regional Customer Service,
visit our website at www.te.com

TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks. Other logos, product and/or company names may be trademarks of their respective owners.



408-2049-29
29 OCT 14 Rev F
CU

**PLASTI-GRIP* Pressure Type
Straight and 90-Degree Bent
Terminals (Use Tooling for
AMPLI-BOND* Connectors)**

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

600 Volts Max

105 °C [222 °F] Max

UL and CSA Wire Combinations



Recognized Under the
Component Program of
UL File E13288



LR 7189
CERTIFIED

8-2/0 AWG
Stranded Wire

8-2/0 AWG
Solid or Stranded Wire

Note: Only certain terminal part numbers apply.

©2014 TE Connectivity family of companies
All Rights Reserved
*Trademark

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752

For latest revision and Regional Customer Service,
visit our website at www.te.com

TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks. Other logos, product and/or company names may be trademarks of their respective owners.



408-2049-29
29 OCT 14 Rev F
CU

**PLASTI-GRIP* Pressure Type
Straight and 90-Degree Bent
Terminals (Use Tooling for
AMPLI-BOND* Connectors)**

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

600 Volts Max

105 °C [222 °F] Max

UL and CSA Wire Combinations



Recognized Under the
Component Program of
UL File E13288



LR 7189
CERTIFIED

8-2/0 AWG
Stranded Wire

8-2/0 AWG
Solid or Stranded Wire

Note: Only certain terminal part numbers apply.

©2014 TE Connectivity family of companies
All Rights Reserved
*Trademark

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752

For latest revision and Regional Customer Service,
visit our website at www.te.com

TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks. Other logos, product and/or company names may be trademarks of their respective owners.



408-2049-29
29 OCT 14 Rev F
CU

**PLASTI-GRIP* Pressure Type
Straight and 90-Degree Bent
Terminals (Use Tooling for
AMPLI-BOND* Connectors)**

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

600 Volts Max

105 °C [222 °F] Max

UL and CSA Wire Combinations



Recognized Under the
Component Program of
UL File E13288



LR 7189
CERTIFIED

8-2/0 AWG
Stranded Wire

8-2/0 AWG
Solid or Stranded Wire

Note: Only certain terminal part numbers apply.

©2014 TE Connectivity family of companies
All Rights Reserved
*Trademark

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752

For latest revision and Regional Customer Service,
visit our website at www.te.com

TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks. Other logos, product and/or company names may be trademarks of their respective owners.