



Pressure Type Wire Connectors
Wire Combinations
PLASTI-GRIP® Splices
(Use Tooling for PLASTI-GRIP Splices)

408-2049-38
21 APR 11 Rev B
CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS



105 °C [222 °F] Max Polyvinyl Chloride (PVC)



WIRE SIZE (AWG) RANGE	WIRE TYPE	SPLICE TYPE	SPLICE RATING
22-16	Solid or Stranded	Butt and Parallel	600 Volts Max 1000 Volts Fixtures and Signs
16-14	Solid or Stranded		
12-10	12-10 Stranded and 12 Solid		

Note: Splices used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928 (formerly MIL-T-7928).

©2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company
All Rights Reserved
*Trademark
TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.
www.te.com

LOC B

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
For latest revision and Regional Customer Service, visit our website at



Pressure Type Wire Connectors
Wire Combinations
PLASTI-GRIP® Splices
(Use Tooling for PLASTI-GRIP Splices)

408-2049-38
21 APR 11 Rev B
CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS



105 °C [222 °F] Max Polyvinyl Chloride (PVC)



WIRE SIZE (AWG) RANGE	WIRE TYPE	SPLICE TYPE	SPLICE RATING
22-16	Solid or Stranded	Butt and Parallel	600 Volts Max 1000 Volts Fixtures and Signs
16-14	Solid or Stranded		
12-10	12-10 Stranded and 12 Solid		

Note: Splices used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928 (formerly MIL-T-7928).

©2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company
All Rights Reserved
*Trademark
TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.
www.te.com

LOC B

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
For latest revision and Regional Customer Service, visit our website at



Pressure Type Wire Connectors
Wire Combinations
PLASTI-GRIP® Splices
(Use Tooling for PLASTI-GRIP Splices)

408-2049-38
21 APR 11 Rev B
CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS



105 °C [222 °F] Max Polyvinyl Chloride (PVC)



WIRE SIZE (AWG) RANGE	WIRE TYPE	SPLICE TYPE	SPLICE RATING
22-16	Solid or Stranded	Butt and Parallel	600 Volts Max 1000 Volts Fixtures and Signs
16-14	Solid or Stranded		
12-10	12-10 Stranded and 12 Solid		

Note: Splices used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928 (formerly MIL-T-7928).

©2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company
All Rights Reserved
*Trademark
TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.
www.te.com

LOC B

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
For latest revision and Regional Customer Service, visit our website at



Pressure Type Wire Connectors
Wire Combinations
PLASTI-GRIP® Splices
(Use Tooling for PLASTI-GRIP Splices)

408-2049-38
21 APR 11 Rev B
CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS



105 °C [222 °F] Max Polyvinyl Chloride (PVC)



WIRE SIZE (AWG) RANGE	WIRE TYPE	SPLICE TYPE	SPLICE RATING
22-16	Solid or Stranded	Butt and Parallel	600 Volts Max 1000 Volts Fixtures and Signs
16-14	Solid or Stranded		
12-10	12-10 Stranded and 12 Solid		

Note: Splices used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928 (formerly MIL-T-7928).

©2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company
All Rights Reserved
*Trademark
TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.
www.te.com

LOC B

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
For latest revision and Regional Customer Service, visit our website at