

80% Width — Each label must be 2.8 inches exact



**Pressure Type Wire Connector  
Combinations Pre-Insulated  
Heat Sealable DuraSeal® Splices  
(Use Tool 55893-1 or 607949-1)**

**408-8628**  
16 MAY 12 Rev B

**CU**

TO BE SOLD ONLY  
WITH INSTALLATION  
INSTRUCTIONS



125°C [257°F] Max  
600 Vac Max  
(1000 Vac Max Fixture Plus Signs)

Heat crimped splice  
with heat gun until  
tubing recovers and  
adhesive melts  
and flows.

Solid or Stranded Wire	
WIRE SIZE (AWG) RANGE	STRIP LENGTH
22- 16	9.52 mm [3/8 in.]
16- 14	
12- 10	

©2012 Tyco Electronics Corporation, a TE Connectivity Ltd. company  
\*Trademark  
TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.  
Other logo and company names may be trademarks of their respective owners.

TOOLING ASSISTANCE  
CENTER 1-800-722-1111  
PRODUCT INFORMATION  
1-800-522-6752



**Pressure Type Wire Connector  
Combinations Pre-Insulated  
Heat Sealable DuraSeal® Splices  
(Use Tool 55893-1 or 607949-1)**

**408-8628**  
16 MAY 12 Rev B

**CU**

TO BE SOLD ONLY  
WITH INSTALLATION  
INSTRUCTIONS



125°C [257°F] Max  
600 Vac Max  
(1000 Vac Max Fixture Plus Signs)

Heat crimped splice  
with heat gun until  
tubing recovers and  
adhesive melts  
and flows.

Solid or Stranded Wire	
WIRE SIZE (AWG) RANGE	STRIP LENGTH
22- 16	9.52 mm [3/8 in.]
16- 14	
12- 10	

©2012 Tyco Electronics Corporation, a TE Connectivity Ltd. company  
\*Trademark  
TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.  
Other logo and company names may be trademarks of their respective owners.

TOOLING ASSISTANCE  
CENTER 1-800-722-1111  
PRODUCT INFORMATION  
1-800-522-6752



**Pressure Type Wire Connector  
Combinations Pre-Insulated  
Heat Sealable DuraSeal® Splices  
(Use Tool 55893-1 or 607949-1)**

**408-8628**  
16 MAY 12 Rev B

**CU**

TO BE SOLD ONLY  
WITH INSTALLATION  
INSTRUCTIONS



125°C [257°F] Max  
600 Vac Max  
(1000 Vac Max Fixture Plus Signs)

Heat crimped splice  
with heat gun until  
tubing recovers and  
adhesive melts  
and flows.

Solid or Stranded Wire	
WIRE SIZE (AWG) RANGE	STRIP LENGTH
22- 16	9.52 mm [3/8 in.]
16- 14	
12- 10	

©2012 Tyco Electronics Corporation, a TE Connectivity Ltd. company  
\*Trademark  
TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.  
Other logo and company names may be trademarks of their respective owners.

TOOLING ASSISTANCE  
CENTER 1-800-722-1111  
PRODUCT INFORMATION  
1-800-522-6752



**Pressure Type Wire Connector  
Combinations Pre-Insulated  
Heat Sealable DuraSeal® Splices  
(Use Tool 55893-1 or 607949-1)**

**408-8628**  
16 MAY 12 Rev B

**CU**

TO BE SOLD ONLY  
WITH INSTALLATION  
INSTRUCTIONS



125°C [257°F] Max  
600 Vac Max  
(1000 Vac Max Fixture Plus Signs)

Heat crimped splice  
with heat gun until  
tubing recovers and  
adhesive melts  
and flows.

Solid or Stranded Wire	
WIRE SIZE (AWG) RANGE	STRIP LENGTH
22- 16	9.52 mm [3/8 in.]
16- 14	
12- 10	

©2012 Tyco Electronics Corporation, a TE Connectivity Ltd. company  
\*Trademark  
TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.  
Other logo and company names may be trademarks of their respective owners.

TOOLING ASSISTANCE  
CENTER 1-800-722-1111  
PRODUCT INFORMATION  
1-800-522-6752



**Pressure Type Wire Connector  
Combinations Pre-Insulated  
Heat Sealable DuraSeal® Splices  
(Use Tool 55893-1 or 607949-1)**

**408-8628**  
16 MAY 12 Rev B

**CU**

TO BE SOLD ONLY  
WITH INSTALLATION  
INSTRUCTIONS



125°C [257°F] Max  
600 Vac Max  
(1000 Vac Max Fixture Plus Signs)

Heat crimped splice  
with heat gun until  
tubing recovers and  
adhesive melts  
and flows.

Solid or Stranded Wire	
WIRE SIZE (AWG) RANGE	STRIP LENGTH
22- 16	9.52 mm [3/8 in.]
16- 14	
12- 10	

©2012 Tyco Electronics Corporation, a TE Connectivity Ltd. company  
\*Trademark  
TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.  
Other logo and company names may be trademarks of their respective owners.

TOOLING ASSISTANCE  
CENTER 1-800-722-1111  
PRODUCT INFORMATION  
1-800-522-6752



**Pressure Type Wire Connector  
Combinations Pre-Insulated  
Heat Sealable DuraSeal® Splices  
(Use Tool 55893-1 or 607949-1)**

**408-8628**  
16 MAY 12 Rev B

**CU**

TO BE SOLD ONLY  
WITH INSTALLATION  
INSTRUCTIONS



125°C [257°F] Max  
600 Vac Max  
(1000 Vac Max Fixture Plus Signs)

Heat crimped splice  
with heat gun until  
tubing recovers and  
adhesive melts  
and flows.

Solid or Stranded Wire	
WIRE SIZE (AWG) RANGE	STRIP LENGTH
22- 16	9.52 mm [3/8 in.]
16- 14	
12- 10	

©2012 Tyco Electronics Corporation, a TE Connectivity Ltd. company  
\*Trademark  
TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.  
Other logo and company names may be trademarks of their respective owners.

TOOLING ASSISTANCE  
CENTER 1-800-722-1111  
PRODUCT INFORMATION  
1-800-522-6752



**Pressure Type Wire Connector  
Combinations Pre-Insulated  
Heat Sealable DuraSeal® Splices  
(Use Tool 55893-1 or 607949-1)**

**408-8628**  
16 MAY 12 Rev B

**CU**

TO BE SOLD ONLY  
WITH INSTALLATION  
INSTRUCTIONS



125°C [257°F] Max  
600 Vac Max  
(1000 Vac Max Fixture Plus Signs)

Heat crimped splice  
with heat gun until  
tubing recovers and  
adhesive melts  
and flows.

Solid or Stranded Wire	
WIRE SIZE (AWG) RANGE	STRIP LENGTH
22- 16	9.52 mm [3/8 in.]
16- 14	
12- 10	

©2012 Tyco Electronics Corporation, a TE Connectivity Ltd. company  
\*Trademark  
TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.  
Other logo and company names may be trademarks of their respective owners.

TOOLING ASSISTANCE  
CENTER 1-800-722-1111  
PRODUCT INFORMATION  
1-800-522-6752



**Pressure Type Wire Connector  
Combinations Pre-Insulated  
Heat Sealable DuraSeal® Splices  
(Use Tool 55893-1 or 607949-1)**

**408-8628**  
16 MAY 12 Rev B

**CU**

TO BE SOLD ONLY  
WITH INSTALLATION  
INSTRUCTIONS



125°C [257°F] Max  
600 Vac Max  
(1000 Vac Max Fixture Plus Signs)

Heat crimped splice  
with heat gun until  
tubing recovers and  
adhesive melts  
and flows.

Solid or Stranded Wire	
WIRE SIZE (AWG) RANGE	STRIP LENGTH
22- 16	9.52 mm [3/8 in.]
16- 14	
12- 10	

©2012 Tyco Electronics Corporation, a TE Connectivity Ltd. company  
\*Trademark  
TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.  
Other logo and company names may be trademarks of their respective owners.

TOOLING ASSISTANCE  
CENTER 1-800-722-1111  
PRODUCT INFORMATION  
1-800-522-6752