



TO BE SOLD  
ONLY WITH  
INSTALLATION  
INSTRUCTIONS

**Pressure Type Wire Connectors  
PLASTI-GRIP\* Vinyl Terminals and  
Butt and Parallel Splices**  
(Use Tooling for PLASTI-GRIP\* Connectors,  
PIDG\* Tool, or TETRA-CRIMP\*‡ Tool)

**408-8787**  
02 MAY 11 Rev B  
**CU**



**UL Listed Wire Combinations  
Wire Sizes 22- 12 AWG**

WIRE		CONNECTOR RATING
SIZE RANGE (AWG)	TYPE	
22-10‡‡	SOLID OR STRANDED	90°C [194°F] Max (Vinyl) 600 Volts Max Building Wiring 1000 V Fixture or Sign
12	SOLID	

**NOTE:** Terminals used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928 (formerly MIL-T-7928).

‡ This tool crimps a terminal with stranded wire only.  
‡‡ Only use stranded wire size 12 AWG with spring spade terminals.

©2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company  
All Rights Reserved  
\*Trademark

TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks. Other logos, product and/or Company names may be trademarks of their respective owners.

TOOLING ASSISTANCE CENTER 1-800-722-1111  
PRODUCT INFORMATION 1-800-522-6752  
For Regional Customer Service, visit our website at [www.te.com](http://www.te.com)

1518274-1



TO BE SOLD  
ONLY WITH  
INSTALLATION  
INSTRUCTIONS

**Pressure Type Wire Connectors  
PLASTI-GRIP\* Vinyl Terminals and  
Butt and Parallel Splices**  
(Use Tooling for PLASTI-GRIP\* Connectors,  
PIDG\* Tool, or TETRA-CRIMP\*‡ Tool)

**408-8787**  
02 MAY 11 Rev B  
**CU**



**UL Listed Wire Combinations  
Wire Sizes 22-12 AWG**

WIRE		CONNECTOR RATING
SIZE RANGE (AWG)	TYPE	
22-10‡‡	SOLID OR STRANDED	90°C [194°F] Max (Vinyl) 600 Volts Max Building Wiring 1000 V Fixture or Sign
12	SOLID	

**NOTE:** Terminals used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928 (formerly MIL-T-7928).

‡ This tool crimps a terminal with stranded wire only.  
‡‡ Only use stranded wire size 12 AWG with spring spade terminals.

©2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company  
All Rights Reserved  
\*Trademark

TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks. Other logos, product and/or Company names may be trademarks of their respective owners.

TOOLING ASSISTANCE CENTER 1-800-722-1111  
PRODUCT INFORMATION 1-800-522-6752  
For Regional Customer Service, visit our website at [www.te.com](http://www.te.com)

1518274-1



TO BE SOLD  
ONLY WITH  
INSTALLATION  
INSTRUCTIONS

**Pressure Type Wire Connectors  
PLASTI-GRIP\* Vinyl Terminals and  
Butt and Parallel Splices**  
(Use Tooling for PLASTI-GRIP\* Connectors,  
PIDG\* Tool, or TETRA-CRIMP\*‡ Tool)

**408-8787**  
02 MAY 11 Rev B  
**CU**



**UL Listed Wire Combinations  
Wire Sizes 22- 12 AWG**

WIRE		CONNECTOR RATING
SIZE RANGE (AWG)	TYPE	
22-10‡‡	SOLID OR STRANDED	90°C [194°F] Max (Vinyl) 600 Volts Max Building Wiring 1000 V Fixture or Sign
12	SOLID	

**NOTE:** Terminals used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928 (formerly MIL-T-7928).

‡ This tool crimps a terminal with stranded wire only.  
‡‡ Only use stranded wire size 12 AWG with spring spade terminals.

©2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company  
All Rights Reserved  
\*Trademark

TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks. Other logos, product and/or Company names may be trademarks of their respective owners.

TOOLING ASSISTANCE CENTER 1-800-722-1111  
PRODUCT INFORMATION 1-800-522-6752  
For Regional Customer Service, visit our website at [www.te.com](http://www.te.com)

1518274-1



TO BE SOLD  
ONLY WITH  
INSTALLATION  
INSTRUCTIONS

**Pressure Type Wire Connectors  
PLASTI-GRIP\* Vinyl Terminals and  
Butt and Parallel Splices**  
(Use Tooling for PLASTI-GRIP\* Connectors,  
PIDG\* Tool, or TETRA-CRIMP\*‡ Tool)

**408-8787**  
02 MAY 11 Rev B  
**CU**



**UL Listed Wire Combinations  
Wire Sizes 22-12 AWG**

WIRE		CONNECTOR RATING
SIZE RANGE (AWG)	TYPE	
22-10‡‡	SOLID OR STRANDED	90°C [194°F] Max (Vinyl) 600 Volts Max Building Wiring 1000 V Fixture or Sign
12	SOLID	

**NOTE:** Terminals used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928 (formerly MIL-T-7928).

‡ This tool crimps a terminal with stranded wire only.  
‡‡ Only use stranded wire size 12 AWG with spring spade terminals.

©2011 Tyco Electronics Corporation, a TE Connectivity Ltd. Company  
All Rights Reserved  
\*Trademark

TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks. Other logos, product and/or Company names may be trademarks of their respective owners.

TOOLING ASSISTANCE CENTER 1-800-722-1111  
PRODUCT INFORMATION 1-800-522-6752  
For Regional Customer Service, visit our website at [www.te.com](http://www.te.com)

1518274-1