



- FOLLOWING CONTACTS ARE INCLUDED AND LOADED:
 SIZE 22: AMP P/N 211431-6; QTY=250
 SIZE 20: AMP P/N 446546-3; QTY=4
 SIZE 16: AMP P/N 446547-3; QTY=3
 SIZE 12: AMP P/N 446548-3; QTY=4
 SIZE 5 COAX: 447335-2; QTY=2
 SIZE 1 COAX WITH OSP ADAPTER: 1218713-1; QTY=8
- POLARIZING KEYS ARE INSTALLED IN POSITION 40.

- WITH CONTACTS FULLY SEATED IN CAVITIES.
- INSERT MATERIAL: DIE CAST ALUMINUM PER ASTM-B-85. INSERT FINISH: CHROMATE PER MIL-C-5541
- INSERT MATERIAL: GLASS EPOXY OR POLYPHENYLENE SULFIDE PER MIL-M-24519.
- SCREWS MAY HAVE TWO WASHERS

445718-8
 PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C.C.THOMAS 11-10-00	Tyco Electronics Corporation Harrisburg, PA 17105-3608																			
DIMENSIONS: INCHES		CHK S.GLATFELTER 11-10-00	NAME S.GLATFELTER																			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD S.GLATFELTER 11-10-00	PRODUCT SPEC																			
<table border="1"> <tr><td>0 PLC</td><td>±</td><td>-</td></tr> <tr><td>1 PLC</td><td>±</td><td>-</td></tr> <tr><td>2 PLC</td><td>±</td><td>-</td></tr> <tr><td>3 PLC</td><td>±</td><td>-</td></tr> <tr><td>4 PLC</td><td>±</td><td>-</td></tr> <tr><td>ANGLES</td><td>±</td><td>-</td></tr> </table>		0 PLC	±	-	1 PLC	±	-	2 PLC	±	-	3 PLC	±	-	4 PLC	±	-	ANGLES	±	-	APPLICATION SPEC		
0 PLC	±	-																				
1 PLC	±	-																				
2 PLC	±	-																				
3 PLC	±	-																				
4 PLC	±	-																				
ANGLES	±	-																				
MATERIAL SEE CALLOUTS		WEIGHT																				
FINISH SEE CALLOUTS		SIZE CAGE CODE DRAWING NO A1 00779 C=445718-8																				
CUSTOMER DRAWING		RESTRICTED TO																				
SCALE 1.5:1		SHEET 1 OF 1 REV F																				