

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

LOC

DIST

REVISIONS

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

CM

00

P	LTR	DESCRIPTION	DATE	DWN	APVD
	MI	REVISED PER ECO-11-005027	17MAR2011	RK	HMR
	N	REVISED PER ECN-21-105427	04JUN2021	WLS	VS
	P	REVISED PER ECN-23-225881	09AUG2023	WLS	VS

30.48
[1.200]24.64
[.970]15.62
[.615]

1. TO BE USED WITH MATE-N-LOK™ PINS

2. MATES WITH PLUG 480349.

3 RIBS ARE OPTIONAL CONSTRUCTION
AND MAY NOT APPEAR ON PART.

 $\phi 6.10$
[.240]

 $\phi 5.21-5.71$
[.205-.225]

 $\phi 7.62$
[.300]

BLUE	1-480350-6
RED	1-480350-2
NATURAL	1-480350-0
COLOR	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 22-MAR-2002

K. WHITAKER

CHK 22-MAR-2002

D. COLEY

APVD 22-MAR-2002

D. COLEY

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING


 TE Connectivity

 NAME
 CAP,
 SINGLE CIRCUIT,
 COMMERCIAL MATE-N-LOK(TM)


SIZE CAGE CODE DRAWING NO RESTRICTED TO

A3 00779 C-480350

SCALE 5:1 SHEET 1 OF 1 REV P


 DIMENSIONS:
 mm [INCHES]

 TOLERANCES UNLESS
 OTHERWISE SPECIFIED:



0 PLC	±-
1 PLC	±-
2 PLC	±0.13 [.005]
3 PLC	±-
4 PLC	±-
ANGLES	±-
FINISH	-

 MATERIAL
 NYLON,
 94V-2



1470-19 (3/11)