


CUSTOMER DRAWING



Product Name	Product Dimensions			Cable Dimensions					
	ϕA min	ϕB min	L max	D max	ϕE min	ϕF min	ϕG max	H ± 0.5	J ± 0.5
CWT-3-S	2.5	3	18.5	3	1.5	1	2.5	7	6
CWT-5-S	4.3	4.8	18.5	4.8	2	1.5	4.3	7	6
CWT-7-S	6.8	7.3	21	7.3	3.3	2.8	6.8	9	8
CWT-11-S	10.8	11.5	28.5	11.5	4.5	4	10.8	9	8


MATERIALS

- INSULATION SLEEVE: Heat-shrinkable, transparent clear, radiation cross-linked modified polyolefin.
- SOLDER PREFORM WITH FLUX:
SOLDER: TYPE Cd18 per ANSI-J-STD-006.
FLUX: TYPE ROM1 per ANSI-J-STD-004.
- MELTABLE SEALING RINGS: Thermally stabilized thermoplastic. Color:blue.


APPLICATION

- These controlled soldering devices are designed for termination of a bare or tin-plated copper shield on a cable having an insulation rated for at least +105°C.
- Temperature range: -55°C to +125°C. For installation procedure and application equipment, consult RPIP-824-00.

For best results, prepare the cable as shown:



TE Connectivity, TE connectivity (logo), Raychem, and SolderSleeve are trademarks

		Raychem		TITLE: SOLDERSLEEVE SHIELD TERMINATOR LOW TEMPERATURE	
Unless otherwise specified dimensions are in millimeters. Inches dimensions are in between brackets.				DOCUMENT NO.: CWT-XX-S	
TOLERANCES: 0.00 N/A 0.0 N/A 0 N/A	ANGLES: N/A ROUGHNESS IN MICRON	TE Connectivity reserves the right to amend this drawing at any time. Users should evaluate the suitability of the product for their application.		Revision: 4	Issue Date: April 2020
DRAWN BY: L. RODRIGUEZ	DATE: 11-20-02	ECO: ECO-20-004959	SCALE: None	SIZE: A	SHEET: 1 of 1