



VS309-11N VS Series-Level Sensor

Features

- ◆ High or low level sensing
- ◆ Internal fitting
- ◆ Reed Switch reliability
- ◆ Nitrile Sealing washer
- ◆ Easy installation

Comments

- ◆ Normally open or normally closed by float inversion
- ◆ Suitable for a wide range of liquids
- ◆ Interface option available
- ◆ Nylon 6.6 Material

Applications

- ◆ Chemical high or low level
- ◆ Diesel Fuel
- ◆ Fuel low level
- ◆ Alcohols
- ◆ Low Oil Detection

Material

Housing/Shuttle Material Glass Filled Nylon 6.6 Glass Filled Nylon 6.6 Float Material

Contact Material Ruthenium Float SG 0.74 Operating Temperature °C -30 to 130

Fuels, Oils, Alcohols Medium

Housing and Float Color Blue

Cable

Cable Length 2 x 0.5M single insulated Stripped Cables **Connection Type**

Cable Type 22 AWG 16/0.2mm PVC insulated Cable Color

Black

Mechanical Specifications

Shock 50g for 11mS duration Vibration 35g up to 500Hz **Maximum Pressure** 4.7 Bar **Float Diameter** 22mm IΡ IP65

Mounting

Thread	M16
Fitment	Internal
Mounting	Vertical


Switching

Contact Form

Switch Action (Reed Switch) SPST Max Switching Voltage VDC 200 Max Switching Voltage VAC 250 **Max Switching Current Amps Max Switching Load Watt** 70 **Operate Mode** N/C with float at bottom stop

Α

Technical Drawing



NORTH AMERICA

Measurement Specialties, Inc., a TE Connectivity Company Phone +1-800-522-6752 Email: customercare.hmpt@te.com

EUROPE

MEAS Deutschland GmbH(Europe) a TE Connectivity Company Phone: +49-800-440-5100 Email: <u>customercare.tlse@te.com</u>

Measurement Specialties (China), Ltd., a TE Connectivity Company Phone: +86-0400-820-6015 Email: <u>customercare.shzn@te.com</u>

TE.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Accustar, American Sensor Technologies, AST, ATEXIS, DEUTSCH, IdentiCal, TruBlue, KPSI, Krystal Bond, Microfused, UltraStable, Measurement Specialties, MEAS, Schaevitz, TE Connectivity, TE, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, product and company names mentioned herein may be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.