File E28476 Project 95ME17303

Issued: June 26, 1995 Revised: February 19, 2010

REPORT

On

*COMPONENT - CONNECTORS FOR USE IN DATA, SIGNAL, CONTROL AND POWER APPLICATIONS

AMP Inc. Harrisburg, PA

Copyright © 1995 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce this Report provided it is reproduced in its entirety.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce that portion of this Report consisting of this Cover Page through Page 2.

File E28476	Vol. 23	Sec. 46	Page 1	Issued:	1995-06-26
	Vol. 94	Sec. 4		Revised:	2022-07-27
	Vol. 98	Sec. 11			
	Vol. 116	Sec. 37			
	Vol. 120	Sec. 15			
		and Report			

$\underline{\mathsf{D}} \ \underline{\mathsf{E}} \ \underline{\mathsf{S}} \ \underline{\mathsf{C}} \ \underline{\mathsf{R}} \ \underline{\mathsf{I}} \ \underline{\mathsf{P}} \ \underline{\mathsf{T}} \ \underline{\mathsf{I}} \ \underline{\mathsf{O}} \ \underline{\mathsf{N}}$

PRODUCT COVERED:

USR Component Connectors - AMP Power Double Lock Connector.

GENERAL:

These devices are multi-pole connectors employing contacts of the solder and crimp termination type for use with printed circuit board.

Products designated USR have been determined to comply with the US requirements referenced in the Test Record.

ENGINEERING CONSIDERATIONS (NOT FOR UL REPRESENTATIVE USE):

<u>Use</u> - For use only in complete equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc.

<u>Conditions of Acceptability</u> - In order to be judged acceptable as a component of electrical equipment, the following conditions should be met.

1. These devices should be used only where they will not interrupt the current.

2. These devices have not been tested for current-carrying capability.

3. The suitability of the mounting means shall be determined in the end use.

4. The placement of these devices within the equipment enclosure should be such that spacings between the live parts and the equipment are suitable for the particular application.

5. The suitability of the min 1.41 mm (0.056 in) spacings between live parts of opposite polarity (including adjacent poles) and between live parts and exposed dead metal parts shall be determined in the end use. Dielectric testing has not been performed.

6. The placement of these devices within the equipment enclosure should be such that spacings between the live parts and the equipment are suitable for the particular application.

File E28476	Vol. 23	Sec. 46	Page 2	Issued:	1995-06-26
	Vol. 94	Sec. 4		Revised:	2012-11-12
	Vol. 98	Sec. 11			
	Vol. 116	Sec. 37			
	Vol. 120	Sec. 15			
		and Report			

7. The electrical and mechanical contact between the connector and the printed circuit board is to be judged in the end-use equipment.

8. The electrical and mechanical suitability of the wiring terminals shall be determined in the end-use. These devices have not been evaluated for conductor secureness testing.

9. Optional accessories such as lock plates have not been evaluated and should be judged in the end-use application.

10. The suitability of the insulating materials used in the molded bodies shall be judged in the end-use equipment.

* 11. The operating temperature of these devices should not exceed the temperature ratings of the insulating materials. These materials may be used interchangeably at a maximum temperature of $105^{\circ}C$.