



产品认证证书

证书编号: CQC08001025528

发证日期: 2023年08月03日
有效期至: 2027年01月21日

委托人名称 泰科电子(深圳)有限公司
及注册地址 深圳市宝安区石岩街道泰科电子科技园

制造商名称 泰科电子(深圳)有限公司
及注册地址 深圳市宝安区石岩街道泰科电子科技园

生产企业名称 泰科电子(深圳)有限公司
及生产地址 深圳市宝安区石岩街道泰科电子科技园

产品名称和系列、规格、型号 继电器
OJT 系列 触点负载: 5A 250VAC (DM/LM); 8A 250VAC(HM); 线圈(DM/LM): 5VDC、6VDC、9VDC、12VDC、24VDC; 线圈(HM): 5VDC、12VDC、24VDC; 线圈功耗: 0.25W(LM);0.45W(DM/HM); 电气寿命: 10000 周期; 机械寿命: 200000 周期; 环境温度: -30°C~85°C; RTII、RTIII; 适用于海拔 5000 米及以下。

产品标准和技术要求 GB 4943.1-2022;IEC 61810-1:2015

认证模式 产品型式试验+初次工厂检查+获证后监督

上述产品符合 CQC11-462151-2022 认证规则的要求, 特发此证。
本证书为变更证书, 证书首次颁发日期: 2008 年 09 月 17 日
证书有效期内本证书的有效性依据发证机构的定期监督获得保持。

可通过扫描下方二维码或登录国家认监委网站 (www.cnca.gov.cn) 查验证书信息



签发: 谢肇煦



中国质量认证中心





产品认证证书

证书编号: CQC08001025528

第 1 页 共 1 页

本证书及附件应同时使用, 信息查验说明见证书页

纸号:

OJT	-**	-1	**	**	*	*****
						代码: 6 位数字或字母代码
						绝缘等级: 空白或 F 或 WG: F 级 155
						线圈功耗: DM - 450mW LM - 250mW HM- 450 mW
						线圈电压: 03:3V 05:5V 06:6V 09:9V 12:12V 18:18V 24:24V 48:48V (HM 仅包含 5V 12V 24V 线圈电压)
						极 数: 1: 单极
						密封结构: SS: 有通气孔; SH: 外壳点胶密封 (HM 仅包含 SS 型, 有通气孔)
						产品基本型号: OJT



中国质量认证中心



CERTIFICATE OF PRODUCT CERTIFICATION

CERTIFICATE NO.: CQC08001025528

Valid from: Aug.03,2023

Valid until:Jan.21,2027

NAME AND REGISTERED ADDRESS OF THE APPLICANT Tyco Electronics (shenzhen) Co., Ltd
Tyco Electronics Technology Park,Shiyan Town,Baoan District,Shenzhen, Guangdong, P.R.China

NAME AND REGISTERED ADDRESS OF THE MANUFACTURER Tyco Electronics (shenzhen) Co., Ltd
Tyco Electronics Technology Park,Shiyan Town,Baoan District,Shenzhen, Guangdong, P.R.China

NAME AND LOCATION OF THE FACTORY Tyco Electronics (shenzhen) Co., Ltd
Tyco Electronics Technology Park,Shiyan Town,Baoan District,Shenzhen, Guangdong, P.R.China

PRODUCT NAME, MODEL AND SPECIFICATION Relay
OJT series Contact loads: 5A 250VAC (DM/LM); 8A 250VAC(HM); Coil voltage(DM/LM) : 5VDC, 6VDC, 9VDC, 12VDC, 24VDC; Coil voltage(HM) : 5VDC, 12VDC, 24VDC ; Coil power : 0.25W(LM);0.45W(DM/HM); Electrical endurance : 10000cycles ; Mechanical endurance : 200000cycles ; Ambient temperature : -30°C~85°C ; RTII、RTIII ; Adapt to 5000m and below.

THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS GB 4943.1-2022;IEC 61810-1:2015

TYPE OF CERTIFICATION SCHEMES Type Testing of Product + Initial Factory Inspection + Follow up Factory Inspection

This is to certify that the above mentioned product(s) complies with the requirements of certification rules of CQC11-462151-2022.

Date of original issued: Sep.17,2008

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE





CERTIFICATE OF PRODUCT CERTIFICATION

CERTIFICATE NO. : CQC08001025528

page 1 of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

OJT	-**	-1	**	**	*	*****
						代码: 6位数字或字母代码
						绝缘等级: 空白或F或WG: F级155
						线圈功耗: DM - 450mW LM - 250mW HM- 450 mW
						线圈电压: 03:3V 05:5V 06:6V 09:9V 12:12V 18:18V 24:24V 48:48V (HM 仅包含5V 12V 24V 线圈电压)
						极 数: 1: 单极
						密封结构: SS: 有通气孔; SH: 外壳点胶密封 (HM 仅包含SS型, 有通气孔)
						产品基本型号: OJT



CHINA QUALITY CERTIFICATION CENTRE