

File E28476
Project 4788932328

April 18, 2019

REPORT

on

COMPONENT - Connectors for Use in Data, Signal, Control and Power
Applications

Tyco Electronics Corp
MIDDLETOWN, PA, US

Copyright © 2019 UL LLC

UL LLC authorizes the above named company to reproduce this Report only for purposes as described in the Conclusion. The Report should be reproduced in its entirety; however to protect confidential product information, the Construction Details Descriptive pages may be excluded.

DESCRIPTION

PRODUCT COVERED:

USR, CNR Component Connector -

Series SDL2.5 water proof connector, plug housing Cat. Nos. 2321918-2, 2321918-3, 2321918-4, 2321918-5, 2321918-6 with Contact 2321921-1.

***Series SDL2.5 water proof connector, plug housing Cat. Nos. X-2443729-Y** with contact 2321921-1.

Series SDL2.5 water proof connector, free hanging receptacle housing Cat. Nos. 2321924-2, 2321924-3, 2321924-4, 2321924-5, 2321924-6 with Contact 2321928-1.

***Series SDL2.5 water proof connector free hanging cap housing Cat. Nos. X-2443725-Y** with contact 2443728-1.

Series SDL2.5 water proof connector, panel mount receptacle housing Cat. Nos. 2321926-2, x, 2321926-4, 2321926-5, 2321926-6 with Contact 2321928-1.

***Series SDL2.5 water proof connector, panel mount cap housing Cat. Nos. X-2443727-Y** with contact 2443728-1.

Series SDL 2.5 water proof connector, plug housing, twist n lock Cat. Nos. 2366251-4, 2366250-4

Series SDL 2.5 water proof connector, cap housing Cat. No. 2366249-4

GENERAL:

These devices are multiple connectors intended for factory assembly on copper wire sizes as indicated in Ratings table below where the acceptability of combinations is determined by UL LLC. The devices are identified as follows:

*** USR - Products designated USR have been investigated using US requirements as noted in the Test Record.**

*** CNR - Products designated CNR have been investigated using Canadian requirements as noted in the Test Record.**

RATINGS:

Housing Cat. Nos	Contact Cat. Nos	Voltage Vac/dc	Ampere (A)	Wire Size (AWG)
2321918-2	2321921-1	250	2	26
			3	22-24
2321918-3	2321921-1	250	2	26
			3	22-24
2321918-4	2321921-1	250	2	26
			3	22-24
2321918-5	2321921-1	250	2	26
			3	22-24
2321918-6	2321921-1	250	2	26
			3	22-24
2321924-2	2321928-1	250	2	26
			3	22-24
2321924-3	2321928-1	250	2	26
			3	22-24
2321924-4	2321928-1	250	2	26
			3	22-24
2321924-5	2321928-1	250	2	26
			3	22-24
2321924-6	2321928-1	250	2	26
			3	22-24
2321926-2	2321928-1	250	2	26
			3	22-24
2321926-3	2321928-1	250	2	26
			3	22-24
2321926-4	2321928-1	250	2	26
			3	22-24
2321926-5	2321928-1	250	2	26
			3	22-24
2321926-6	2321928-1	250	2	26
			3	22-24
2366249-4	2321928-1	250	2.5	22
2366250-4	2321921-1	250	2.5	22
2366251-4	2321921-1	250	2.5	22
*X-2443725-Y	2443728-1	250	3	22-24
*X-2443727-Y			2	26
*X-2443729-Y	2321921-1	250	3	22-24
			2	26

Disconnecting Use - see Sec Gen for required marking.

TECHNICAL CONSIDERATIONS (NOT FOR FIELD REPRESENTATIVE'S USE):

Use - For use only in or with complete equipment where the acceptability of the combination is determined by UL LLC.

Conditions of Acceptability - The following are among the considerations to be made when evaluating the device in the end-use product.

Interruption of Current

1. These devices are not suitable for interrupting the flow of current by connecting or disconnecting the mating connector.

Current-Carrying Capability and Current Ratings

2. These devices have been subjected to the Temperature test with the rated currents and maximum temperature rise and recorded temperature (adjusted to 25°C ambient) values tabulated below:

Cat Nos.	Wire Size, AWG	Current, A	Maximum Temperature °C		Represent Cat. Nos.
			Rise	Recorded Temperature	
2321918-6 with contact 2321921-1	24	3	17.3	42.3	2321918-2, 2321918-3, 2321918-4, 2321918-5 with contact 2321921-1
2321924-6 with contact 2321928-1	24	3	18.4	43.4	2321924-2, 2321924-3, 2321924-4, 2321924-5, 2321926-2, 2321926-3, 2321926-4, 2321926-5, 2321926-6 with Contact 2321928-1
2321918-6 with contact 2321921-1	26	2	5.4	30.4	2321918-2, 2321918-3, 2321918-4, 2321918-5 with contact 2321921-1
2321924-6 with contact 2321928-1	26	2	5.4	30.4	2321924-2, 2321924-3, 2321924-4, 2321924-5, 2321926-2, 2321926-3, 2321926-4, 2321926-5, 2321926-6 with Contact 2321928-1
2366249-4 with contact 2321928-1 mated with 2366250-4 with contact 2321921-1	22	2.5	15.02	40.02	2366251-4 with contact 2321921-1

Table Con't

Cat Nos.	Wire Size, AWG	Current, A	Maximum Temperature °C		Represent Cat. Nos.
			Rise	Recorded Temperature	
2443727 (6 positions) mated with 2443729	24	3	15.6	39.2	2443725
2443727 (6 positions) mated with 2443729	26	2	9.1	32.5	2443725
1-2443725-0 (Mated with 1-2443729-0)	24	3	12.0	37.0	1-2443727-0
1-2443729-0 (Mated with 1-2443725-0)	24	3	10.8	35.8	N/A
1-2443725-0 (Mated with 1-2443729-0)	26	2	16.2	41.2	1-2443727-0
1-2443729-0 (Mated with 1-2443725-0)	26	2	16.6	41.6	N/A

Insulating Materials

3. These devices employ insulating materials with properties as tabulated below at the minimum thickness employed in the connector housing, the suitability of the insulating materials based on the documented values shall be determined in the end-use application. Please note the values specified in the table when multiple materials are indicated represent the minimum values for the group of materials.

Mold Stress testing was performed at 115 °C for 7 hours with acceptable results. (Insulating Material A)

* Mold Stress testing was performed at 140 °C for 7 hours with acceptable results. (Insulating Material B) except for Models 2443725, **2443729**, and 2443727 which the test was conducted at **135 °C** for 7 hours with acceptable results.

Mold Stress testing was performed at 115 °C for 7 hours with acceptable results. (Insulating Material C)

Cat. No.	Insulating Material (#)	Measured Minimum Thickness	Flame Class	HWI	HAI	RTI Elec	Max Operating Temp, °C
2321918-2	A or B	0.40 mm	V-0	-	-	130	105
2321918-3	A or B	0.40 mm	V-0	-	-	130	105
2321918-4	A or B	0.40 mm	V-0	-	-	130	105
2321918-5	A or B	0.40 mm	V-0	-	-	130	105
2321918-6	A or B	0.40 mm	V-0	-	-	130	105
2321924-2	A or B	0.40 mm	V-0	-	-	130	105
2321924-3	A or B	0.40 mm	V-0	-	-	130	105
2321924-4	A or B	0.40 mm	V-0	-	-	130	105
2321924-5	A or B	0.40 mm	V-0	-	-	130	105
2321924-6	A or B	0.40 mm	V-0	-	-	130	105
2321926-2	A or B	0.40 mm	V-0	-	-	130	105
2321926-3	A or B	0.40 mm	V-0	-	-	130	105
2321926-4	A or B	0.40 mm	V-0	-	-	130	105
2321926-5	A or B	0.40 mm	V-0	-	-	130	105
2321926-6	A or B	0.40 mm	V-0	-	-	130	105
2366249-4	C	0.60 mm	V-0	0	0	130	105
2366250-4	C	0.60 mm	V-0	0	0	130	105
2366251-4	C	0.60 mm	V-0	0	0	130	105
*X-2443725-Y	B	0.50 mm	V-0	-	-	130	125
*X-2443727-Y	B	0.50 mm	V-0	-	-	130	125
X*-2443729-Y	B	0.40 mm	V-0	-	-	130	125

Note:

(#) - Code for Insulating Body Material.

- A. Tyco RM 2136682.
 - 1. Dielectric strength (kV/mm): 20
 - 2. CTI: 0

- B. Tyco RM 705999.
 - 1. Dielectric strength (kV/mm): 8
 - 2. CTI: 1

- C. Tyco RM 2136700
 - 1. Dielectric strength (kV/mm): 17
 - 2. CTI: 2

Miscellaneous

- 4. The enclosure of the device has live parts that may be exposed to user contact when the connector is energized. The device is suitable for use only within an acceptable enclosure.