File E82292 Project 98SC42762

February 17, 1999
Revised: March 17, 2014

REPORT

ON

COMPONENT - SWITCHES, INDUSTRIAL CONTROL

*

Tyco Electronics (Shenzhen) Co. Ltd Shenzhen Guangdong, China

Copyright © 1999 Underwriters Laboratories Inc.

Underwriters Laboratories Inc. authorizes the above-named company to reproduce this Report provided it is reproduced in its entirety.

Underwriters Laboratories Inc. authorizes the above named company to reproduce that portion of this Report consisting of this Cover Page through Page 2.

File E82292 Vol. 1 Sec. 24 Page 1 Issued: 02-17-99 and Report Revised: 01-22-01

DESCRIPTION

PRODUCT COVERED:

* USR/CNR - Component - Industrial Control Switch, Model TSC-1, followed by two digits 03 through 24, followed by L or D, followed by 3, followed by blank or M, and followed by blank or H.

GENERAL:

These devices are open-type, single-pole, single-throw, magnetically operated relays intended with normally open and normally closed contacts. These devices are for use in Safety of Information Technology Equipment.

RATINGS:

Contact Ratings -

1 A, 120 V ac, resistive, 6,000 cycles

1 A, 30 V dc, 6,000 cycles

Coil Ratings -

3-24 V dc

File E82292 Vol. 1 Sec. 24 Page 2 Issued: 1999-02-17 and Report Revised: 2001-12-13

NOMENCLATURE:

I - Basic model designation

II - Contact form: 1 pole

III - Coil voltage: 03 V dc through 24 V dc

IV - Coil Power Consumption: L - Coil Power 0.15 W D - Coil Power 0.3 W

V - Contact Material: 3 - AgNi (AuAg Alloy Clad)

VI - Contact Configuration: Blank - 1 Form C (Transfer)

M - 1 Form A (N.O.)

VII - Sealing Condition: Blank - Vented (Flux-tight)

H - Plastic sealed

VIII - Terminal Designation: Blank - Standard

S: - SMD with Level type

P: - SMD with Perpendicular type

ENGINEERING CONSIDERATIONS (NOT FOR FIELD REPRESENTATIVE'S USE):

Use - For use only in complete equipment where the acceptability of the combination has been determined by Underwriters Laboratories.

This device has been judged in accordance with the required spacing in the Standard for Safety of Information Technology Equipment (UL 1950), Table 3 and Table 6, and under the requirements for the Outline of Investigation for Relays used in Information Technology Equipment, Subject 508B.