




LOC		DIST		REVISIONS					
AD		00		REV	LYR	DESCRIPTION	DATE	OWN	APVD
				C		REVISED PER ECO-11-025276	27DEC11	KH	DY

- 1 MATERIAL:
HOUSING: LCP, GLASS FILLED, UL94V-0.
TERMINALS: HIGH PERFORMANCE COPPER ALLOY.
- 2 FINISH:
30μ" MIN GOLD IN CONTACT AREA. SELECTIVE TIN
ON PCB TAILS, NICKEL OVERALL.
- 3 FINISH:
30μ" MIN GOLD IN CONTACT AREA. SELECTIVE TIN-LEAD
ON PCB TAILS, NICKEL OVERALL.
4. SCREWS PACKAGED IN END OF PACKAGING TUBE.
- 5 FOR GROUNDED GUIDE PIN USE Ø3.56±0.08 PTH,
Ø3.66 DRILL, AND Ø6.5 PAD.
6. KEYING PIN SHOWN IN POSITION A. SEE KEYING CHART
ON SHEET 2 FOR OTHER POSITIONS.

THIS DRAWING IS A CONTROLLED DOCUMENT.		OWN J. K. SHOBER 07JAN2011	TE Connectivity	
DIMENSIONS:		CHK J. EABY 07JAN2011		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD J. EABY 07JAN2011	NAME IMPACT, 3 PAIR, 16 COLUMN, HEADER	
mm		PRODUCT SPEC	RIGHT GUIDED, LEFT END WALL	
9 PLC ±.1		APPLICATION SPEC	SIGNAL MODULE, 0.46 PTH	
1 PLC ±0.25		SIZE CAGE CODE DRAWING NO	RESTRICTED TO	
2 PLC ±0.13		WEIGHT	A100779C=2007798	
3 PLC ±.1		CUSTOMER DRAWING	SCALE 6:1 SHEET 1 OF 2 REV C	
4 PLC ±.1				
ANGLES ±.1				
FINISH SEE TABLE				

LOC		DIST		REVISIONS					
AD	00	P	LTR	DESCRIPTION			DATE	DWN	APVD
			-	SEE SHEET 1			-	-	-

	H	5.5	8-2007798-6
	H	4.9	8-2007798-5
	H	4.5	8-2007798-4
	H	5.5	8-2007798-3
	H	4.9	8-2007798-2
	H	4.5	8-2007798-1
	G	5.5	7-2007798-6
	G	4.9	7-2007798-5
	G	4.5	7-2007798-4
	G	5.5	7-2007798-3
	G	4.9	7-2007798-2
	G	4.5	7-2007798-1
	F	5.5	6-2007798-6
	F	4.9	6-2007798-5
	F	4.5	6-2007798-4
	F	5.5	6-2007798-3
	F	4.9	6-2007798-2
	F	4.5	6-2007798-1
	E	5.5	5-2007798-6
	E	4.9	5-2007798-5
	E	4.5	5-2007798-4
	E	5.5	5-2007798-3
	E	4.9	5-2007798-2
	E	4.5	5-2007798-1
	D	5.5	4-2007798-6
	D	4.9	4-2007798-5
	D	4.5	4-2007798-4
	D	5.5	4-2007798-3
	D	4.9	4-2007798-2
	D	4.5	4-2007798-1
	C	5.5	3-2007798-6
	C	4.9	3-2007798-5
	C	4.5	3-2007798-4
	C	5.5	3-2007798-3
	C	4.9	3-2007798-2
	C	4.5	3-2007798-1
	B	5.5	2-2007798-6
	B	4.9	2-2007798-5
	B	4.5	2-2007798-4
	B	5.5	2-2007798-3
	B	4.9	2-2007798-2
	B	4.5	2-2007798-1
	A	5.5	1-2007798-6
	A	4.9	1-2007798-5
	A	4.5	1-2007798-4
	A	5.5	1-2007798-3
	A	4.9	1-2007798-2
	A	4.5	1-2007798-1
	-	5.5	2007798-6
	-	4.9	2007798-5
	-	4.5	2007798-4
	-	5.5	2007798-3
	-	4.9	2007798-2
	-	4.5	2007798-1
FINISH	KEY POSITION	DIM M	PART NUMBER

REFER TO WWW.TE.COM
FOR PRODUCT AVAILABILITY

KEY POSITION
CHART

NONE

A

E

B

F

C

G

D

H

THIS DRAWING IS A CONTROLLED DOCUMENT.			DWN	J. K. SHOBER	07JAN2011	TE Connectivity		
			CHK	J. EABY	07JAN2011			
DIMENSIONS:			TOLERANCES UNLESS OTHERWISE SPECIFIED:			NAME	IMPACT, 3 PAIR, 16 COLUMN, HEADER RIGHT GUIDED, LEFT END WALL SIGNAL MODULE, 0.46 PTH	
mm						PRODUCT SPEC		
			9 PLC	±		APPLICATION SPEC	SIZE	CAGE CODE
			3 PLC	±0.25			DRAWING NO	RESTRICTED TO
			5 PLC	±0.13			A100779	C=2007798
			4 PLC	±				
			ANGLES	±				
MATERIAL			FINISH	SEE TABLE		WEIGHT		
-						-		
			CUSTOMER DRAWING			SCALE	5:1	SHEET 2 OF 2
								REV C