Thermofit Molded Parts Specification Control Drawing


Part Number : 202A212 thru 264

Description : Boot, Long

NOTES

1. All dimensions are in $\frac{\text{incres}}{\left[\text{millimeters}\right]}$; [gms]

- 2. Dimensions appearing in table are as follows:
 - a As Supplied
 - b After Unrestricted Recovery
- Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added, entry diameters will be reduced by .06 max.
- Molding ports are optional. When -00 modification number is specified molding ports will be located as shown.
- 5. Weight shown in table of dimensions is based on polyolefin part.






TABLE OF DIMENSIONS										
PART NUMBER	н		J		Р	R	s	w	Weight	
	Min	Max	Min	Max	±10%	Ref	Ref	±20%	Nom	
	a	b	a	ь	b	b	b	b	ь	
202A212	.88	.62	.40	.23	<u>5.00</u>	.62	.50	. <u>08</u>	. <u>018</u>	
	[22,4]	[15,7]	[10,2]	[5,8]	[127,0]	[15,7]	[12,7]	[2,03]	[8,2]	
202A222	.88	.62	.48	. <u>27</u>	<u>5.00</u>	.62	.50	. <u>08</u>	. <u>021</u>	
	[22,4]	[15.7]	[12.2]	[6,9]	[127,0]	[15,7]	[12,7]	[2,03]	[9,5]	
202A233	1.20	.78	.60	.34	<u>5.75</u>	.62	.50	.09	. <u>031</u>	
	[30,5]	[19,8]	[15,2]	[8,6]	[146,1]	[15,7]	[12,7]	[2,29]	[14,1]	
202A243	1.45	.94	.80	. <u>44</u>	6.38	.88	.76	.09	. <u>042</u>	
	[36,8]	[23,9]	[20,3]	[11,2]	[162,1]	[22,4]	[19,3]	[2,29]	[19,1]	
202A254	1.76	1.34	.92	<u>.55</u>	7.06	1.00	.76	.10	. <u>048</u>	
	[44,7]	[34,0]	[23,4]	[14,0]	[179,3]	[25,4]	[19,3]	[2,54]	[21,8]	
202A264	2.26	1.61	1.16	<u>.71</u>	7.06	1.00	<u>.76</u>	.10	. <u>051</u>	
	[57,4]	[40,9]	[29,5]	[18,0]	[179,3]	[25,4]	[19,3]	[2,54]	[23,1]	

Raychem

RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025 (415) 361–6055

Revision: M Date: 3/5/92

Part Number: 202A212 thru 264

Description: Boot, Long

Thermofit Molded Parts Specification Control Drawing


Part Number : 202A212 thru 264

Description: Boot, Long

COMPATABILIT	CHART				
MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION
-3	Polyolefin, Semi-rigid	RT-301	/42; /86	S-1017; S-1048	Adhesive
-4	Polyolefin, Flexible	RT-1304	/42; /86	S-1017; S-1048	Adhesive
-5	Elastomer, Flexible	RT-501	/42	S-1017	Adhesive
-6	Silicone	RT-602	N/A		
-12	*VITON, Flexible	RT-1312	N/A		
-25	Elastomer, Fluid Resistant	RT-1325	N/A		

^{*}VITON is a Registered Trademark of Dupont

If this document is printed it becomes uncontrolled. Check for the latest revision.



THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION

Raychem

RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025 (415) 361-6055

Revision: M Date: 3/5/92

202A212 thru 264 Part Number :

Description : Boot, Long

CAD FILE MP92093