


THIS DRAWING IS UNPUBLISHED.	RELEASED FOR PUBLICATION	20
© COPYRIGHT 20	-	ALL RIGHTS RESERVED.

LOC F	DIST 00	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
			-	SEE SHEET 1	-	-	-

- 1 THIS CONNECTOR MEETS THE REQUIREMENTS OF ASNE 0237 AND MIL- DTL-24308
- 2- INSERT ARRANGEMENT PER MIL- DTL-24308
- 3- MATERIALS :
SHELL : STEEL,ZINC PLATED
HOUSING : PBT,GLASS FILLED,UL94V0
RETAINING CLIP : STAINLESS STEEL OR BERYLLIUM COPPER
GROMMET AND INTERFACIAL SEAL : FLUOROSILICONE ELASTOMER
SEALING COMPOUND : RTV
- 4- MARKINGS:
. MANUFACTURER IDENTIFICATION
. PART NUMBER
. DATE-CODE
- 5- ACCEPTS #20 PIN CRIMP CONTACTS P/N: 205089-1
- 6- CABLES EXTERNAL DIAMETER FOR CONTACTS #20 : Ø0.85 to Ø1.83
- 7- FOR CONTACT CRIMPING INSTRUCTION SHEET REFER TO SPEC IS 7516
FOR CONTACT INSTALATION/ REMOVAL INSTRUCTION SHEET REFER TO SPEC IS 7508
- 8- CRIMP WITH HAND TOOL: 601966-1 + DIE INSERT: 601966-4
- 9- INSERTION/EXTRACTION TOOL P/N: 91067-2

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J.THUEZ	100CT2012	 TE Connectivity			
DIMENSIONS: mm		CHK Y.PETRONIN	100CT2012	NAME PLUG, AMPL, SEALED,ZINC PL SHELL -			
	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±- 1 PLC ±0.5 2 PLC ±0.13 3 PLC ±0.013 4 PLC ±0.0001 ANGLES ±	APVD Y.PETRONIN	100CT2012				
		PRODUCT SPEC NOTE 1		SIZE A 3	CAGE CODE 00779	DRAWING NO C-2091880	RESTRICTED TO -
		APPLICATION SPEC NOTE 8					
MATERIAL NOTE 3	FINISH NOTE 3	WEIGHT -					
Customer Drawing				SCALE 2:1	SHEET 2	OF 2	REV C