

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	REVISED ECR-18-004730	25MAY2018	JC	LSF

KEYING 2

11.8

TABLE 1

PLATING	APPLIED TERMINAL		APPLICABLE WIRE RANGE
	YAZAKI PARTS CO. LTD.	SUMITOMO WIRING SYSTEMS CO. LTD	
TIN	7116-3153-02	8100-3624	0.22~0.35mm ²
GOLD	7116-3153-08	8100-3628	
TIN	7116-3154-02	8100-3625	0.3~0.5mm ²
GOLD	7116-3154-08	8100-3629	
TIN	7116-5096-02	8240-0182	0.13mm ²
GOLD	7116-5096-08	8240-0338	
TIN	-	8240-0602 (ALUMINIUM WIRE)	0.5mm ²
TIN	-	8240-0309 (ALUMINIUM WIRE)	0.75mm ²

KEYING 1

BOX	BAG	KEYING	COLOUR	PART NUMBER
		2	GREY	2237126-2
		1	NATURAL	2237126-1

NOTES:

1 RETAINER SHOULD BE SET TO THE PRE-ASSEMBLY POSITION WITHIN THE PLUG HOUSING WHEN SHIPPED TO CUSTOMER

2. PART NUMBER OF CAP ASSEMBLY:
2237122-1 (KEYING 1)
2237122-2 (KEYING 2)

3. APPLIED TERMINAL: SEE TABLE 1

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD		NAME	
mm				18APR2017		STE	
		0 PLC ±0.3		DWN		TE Connectivity	
		1 PLC ±0.3		CHK			
		2 PLC ±0.3		18APR2017		4P 0.64II PLUG HOUSING ASSY WITH ANTI OVER STRESS	
		3 PLC ±0.3		CHK			
		4 PLC ±0.3		18APR2017		SIZE	
		ANGLES ±3°		APVD		CAGE CODE	
MATERIAL PBT		FINISH SEE TABLE		SE L FONG		DRAWING NO	
				PRODUCT SPEC		A300779	
				APPLICATION SPEC		C=2237126	
				WEIGHT 1.0g		RESTRICTED TO	
				CUSTOMER DRAWING		SCALE 5:1 SHEET 1 OF 1 REV A	

1470-19 (3/13)