

1471-9 (3/13)

		500	1000 + 10/-0	2349831-2
		250	500 +10/-0	2349831-1
		(" <b>M</b> ")	"L"	TE P/N
	CONTROLLED DOCUMENT.	DWN 08JAN2019 Т.SMITH снк 08JAN2019 G.GUTGOLD	-E TE	TE Connectivity
	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±- 1 PLC ±0.5 2 PLC ±0.13 3 PLC ±0.013	APVD - NAME	SLIVER 2.0 1C 33AW STRAIGHT TO STRAIG -	
MATERIAL	4 PLC ±0.0001 ANGLES ±- FINISH - -	WEIGHT - A	200779 C-2349831	RESTRICTED TO - : 1 SHEET 1 OF 3 REV A

THIS DRAWING IS UNPUBLISHED.	RELEASED FOR PUBLICATION
C COPYRIGHT 20 BY -	ALL RIGHTS RESERVED.

4

D

С

В

А

3

20

		P			P2		
	PIN #	PAIR #	DESIGNATION	WIRE TYPE	DESIGNATION	PAIR #	PIN #
Г	— A 1		GROUND	DISCRETE	GROUND		A 1
-	— A 2		GROUND	DISCRETE	GROUND		A 2
	— A 3		GROUND	DISCRETE	GROUND		A 3
COMMONED	— A 4		GROUND	DISCRETE	GROUND		A 4
-	— A 5		GROUND	DISCRETE	GROUND		A 5
L	— A 6		GROUND	DISCRETE	GROUND		A 6
	Α7		SIDE BAND	DISCRETE	SIDE BAND		Α7
	A 8		SIDE BAND	DISCRETE	SIDE BAND		A 8
	A 9		SIDE BAND	DISCRETE	SIDE BAND		A 9
	A 1 0		SIDE BAND	DISCRETE	SIDE BAND		A 1 0
	A 1 1		SIDE BAND	DISCRETE	SIDE BAND		A 1 1
	A 1 2		SIDE BAND	DISCRETE	SIDE BAND		A 1 2
	A 1 3		GND		GND		A 1 3
	A 1 4		CLK	DIFF PAIR	CLK		A 1 4
	A 1 5		CLK	DIFF PAIR	CLK		A 1 5
	A 1 6		GND		GND		A 1 6
	A 1 7	0	РСІеТХ	DIFF PAIR	РСІеТХ	0	A 1 7
	A 1 8	0	PCIe TX	DIFF PAIR	PCIe TX	0	A 1 8
	A 1 9		GND		GND		A 1 9
	A 2 0	1	РСІеТХ	DIFF PAIR	РСІеТХ	1	A 2 0
	A 2 1	1	PCIe TX	DIFF PAIR	PCIe TX	1	A 2 1
	A 2 2		GND		GND		A 2 2
	A 2 3	2	РСІеТХ	DIFF PAIR	РСІеТХ	2	A 2 3
	A 2 4	2	PCIe TX	DIFF PAIR	PCIe TX	2	A 2 4
	A 2 5		GND		GND		A 2 5
	A 2 6	3	РСІеТХ	DIFF PAIR	РСІеТХ	3	A 2 6
	A 2 7	3	PCIe TX	DIFF PAIR	PCIe TX	3	A 2 7
	A 2 8		GND		GND		A 2 8

2

REVISIONS

Р	LTR	DESCRIPTION	DATE	DWN	APVD			
	-	SEE SHEET 1	-	-	-			

1

- COMMONED

THIS PRINT IS
PRELIMINARY
UNQUALIFIED PRODUCT CONTACT PRODUCT ENGINEERING BEFORE USING THIS PRINT

THIS DRAWING IS A C	ONTROLLED DOCUMENT.	CHK CUTCOL 08 JAN 2019	TE Connectivity
DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±- 1 PLC ±0.5 2 PLC ±0.13	G. GUTGOLD APVD - PRODUCT SPEC -	NAME SLIVER 2.0 1C 33AWG 100 OHM STRAIGHT TO STRAIGHT
$\Psi$	3 PLC ±0.013 4 PLC ±0.0001 ANGLES ±-	APPLICATION SPEC -	SIZE CAGE CODE DRAWING NO RESTRICTED TO
MATERIAL –	FINISH -	WEIGHT _	A 2 0 0 7 7 9 C - 2349831 - 0 0 7 7 9 C - 2349831 - 0 0 0 7 7 9 C - 2349831 - 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
_	-	CUSTOMER DRAWING	SCALE 1:1 SHEET 2 OF A

D

С

А

В

4		
THIS DRAWING IS UNPUBLISHED.	RELEASED FOR PUBLICATION	20
C COPYRIGHT 20 BY -	ALL RIGHTS RESERVED.	

		P	P1		F	P2		
	PIN #	PAIR #	DESIGNATION	WIRE TYPE	DESIGNATION	PAIR #	PIN #	
Г	B 1		12V POWER	DISCRETE	12V POWER		B 1	
-	B 2		12V POWER	DISCRETE	12V POWER		B 2	
	<b>B</b> 3		12V POWER	DISCRETE	12V POWER		В3	
IMONED — —	Β4		12V POWER	DISCRETE	12V POWER		B 4	
-	В5		12V POWER	DISCRETE	12V POWER		B 5	
	B 6		12V POWER	DISCRETE	12V POWER		Β6	
	Β7		SIDE BAND	DISCRETE	SIDE BAND		Β7	
	B 8		SIDE BAND	DISCRETE	SIDE BAND		B8	
	В9		SIDE BAND	DISCRETE	SIDE BAND		В9	
	B10		SIDE BAND	DISCRETE	SIDE BAND		B10	
	B 1 1		3.3 AUX POWER	DISCRETE	3.3 AUX POWER		B 1 1	
	B12		SIDE BAND	DISCRETE	SIDE BAND		B 1 2	
	B13		GND		GND		B13	
	B14		CLK	DIFF PAIR	CLK		B 1 4	
	B15		CLK	DIFF PAIR	CLK		B 1 5	
	B16		GND		GND		B16	
	B 1 7	0	PCIeRX	DIFF PAIR	PC I e R X	0	B 1 7	
	B18	0	PCIe RX	DIFF PAIR	PCIe RX	0	B18	
	B 1 9		GND		GND		B19	
	B 2 0	1	PCIeRX	DIFF PAIR	PC I e R X	1	B20	
	B 2 1	1	PCIe RX	DIFF PAIR	PCIe RX	1	B 2 1	
	B 2 2		GND		GND		B 2 2	
	B 2 3	2	PCIeRX	DIFF PAIR	P C I e R X	2	B 2 3	
	B 2 4	2	PCIe RX	DIFF PAIR	PCIe RX	2	B24	
	B 2 5		GND		GND		B 2 5	
	B 2 6	3	PCIeRX	DIFF PAIR	P C I e R X	3	B26	
	B 2 7	3	PCIe RX	DIFF PAIR	PCIe RX	3	B 2 7	
	B28		GND		GND		B28	

3

А

D

С

В

2

- COMMONED

REVISIONS

	REVISIONS								
P	LTR	DESCRIPTION	DATE	DWN	APVD				
	-	SEE SHEET 1	-	-	-				

1

THIS PRINT IS
PRELIMINARY
UNQUALIFIED PRODUCT
CONTACT PRODUCT ENGINEERING BEFORE USING THIS PRINT

	THIS DRAWING IS A C	ONTROLLED DOCUMENT.	DWN 08JAN2019 T.SMITH снк 08JAN2019 G. GUTGOLD	TE Connectivity
	DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±- 1 PLC ±0.5 2 PLC ±0.13 3 PLC ±0.013	- G. GUIGOLD APVD - PRODUCT SPEC - APPLICATION SPEC	NAME SLIVER 2.0 1C 33AWG 100 OHM STRAIGHT TO STRAIGHT -
,	MATERIAL - -	4 PLC ±0.0001 ANGLES ±- FINISH - -		SIZE CAGE CODE DRAWING NO RESTRICTED TO   A 2 0 0 7 7 9 C=2349831 -   SCALE 1:1   SCALE 1:1

\_\_\_\_\_

С

D

В

А