



1. PARTS COMPLY WITH TE SOLDERABILITY
SPEC. NO. 109-11-3
2. CONTACT IS PLATED OVERALL WITH .000050 NICKEL, THEN
.000030 GOLD OVER CONTACT LENGTH INDICATED AND TIN
PLATED ON SOLDER TAIL END.
3. DIMENSION SHOWN REPRESENT PRODUCT IN DRY CONDITION.
ADDITIONAL 2% GROWTH DUE TO END USE LOCATION MOISTURE
ABSORPTION MAY OCCUR AND SHOULD BE ACCOUNTED FOR.

	-2	NATURAL	GOLD /A
6-	-1	BLUE	PRE TIN
2-	-1	RED	
350539-1	NYLON - NATURAL	COPPER ALLOY - PRE-TIN	
ASSEMBLY NO.	HSG MAT'L & COLOR	PIN MAT'L & FINISH	
©1975 BY AMP INCORPORATED. ALL RIGHTS RESERVED. AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING.		CUSTOMER COPY REFERENCE ONLY	
DR <i>g. Edwards</i>	MATERIAL AND FINISH SEE TABLE	TE Connectivity	
CHK <i>J.H.R.S.</i> <i>EM PLTCHARD</i>	WIRE RANGE - INSULATION TELEGRAPHIC CIRCUT AS NOTED S. DTS N. LIST OF	CLIP 084 DIA. PIN POSITIVE LOCK	REV N4
DE <i>T. Kunkle</i>	SCALE 1 IN = 10 MILS	LOC CM B	HD 350539
<i>T. Kunkle</i>	2 CIRCUIT MATE-N-LOK P.C. BOARD HEADER		