SP	ECIFICA	TION CO	NTROLI	DRAW	ING	SCD	44/042X		
Title	TWO CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, OUTER SPACE, 600 VOLT					Date 12-11-15	Revision B		
		This specification sh	eet forms a part of	the latest issue	e of Raychem	Specification 44.			
СС	OMPONENT WIRE	S - 44/041X							
		CABLE CONSTRUCTION DETAILS							
		PART NUMBER <u>1</u> /	CONDUCTOR SIZE (AWG)	OUTSIDE DIAMETER (inch)		MAXIMUM WEIGHT (lbs/1000 ft.)			
		44/042X-26-*	26	.066	.071	2.7			
		44/042X-24-*	24	.078	.083	4.1			

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

22

20

18

16

14

12

TEMPERATURE RATING: 135°C Maximum continuous conductor temperature VOLTAGE RATING: 600 volts (rms) at sea level DIELECTRIC WITHSTAND: 2500 volts (rms), 60 Hz, 1 minute INSULATION FLAWS: Spark Test, 3.0 kV (rms) at 3 kHz Impulse Dielectric Test, 8.0 kV (peak)

44/042X-22-*

44/042X-20-*

44/042X-18-*

44/042X-16-*

44/042X-14-*

44/042X-12-*

1/ PART NUMBER:

.092

.108

.128

.142

.172

.216

The "X" in the part numbers above shall be replaced with a conductor material designator as follows:

- 1 tin-coated copper
- 2 silver-coated copper

.097

.113

.133

.148

.180

.224

3 nickel-coated copper

4 silver-coated high-strength copper alloy (AWG 26-20 only) The "*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors. Example: AWG 20, tin-coated copper conductors;

6.1

9.2

14.3

17.8

28.0

44.3

black and brown component wires: 44/0421-20-0/1

NOTE: Nominal values are for information only. Nominal values are not requirements.

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics Corporation also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.							
1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902" MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.							
Page 1 of 1	Raychem, TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.		Raychem Wire & Cable 501 Oakside Avenue Redwood City, CA 94063-3800 Phone: 1-800-227-8816 Fax: 1-650-361-6297				
	DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL						
	THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.	connectivity					

© 2015 Tyco Electronics Corporation. All rights reserved.