

| | | | | 1 | | | |
|--------------|------|---|-----|---------------------------|-----------|-----|------|
| OC | DIST | | | REVISIONS | | | |
| СМ | 00 | Р | LTR | DESCRIPTION | DATE | DWN | APVD |
| | | | C 6 | REVISED PER ECO-19-013973 | 16SEP2019 | RS | WLS |
| | | | D | REVISED PER ECO-20-013993 | 010CT2020 | WLS | VS |
| | | | | | | | |
| | | | | | | | |
| T I N | | | | | 7 | | |

С

В

- Δ 2.54 μ m MIN BRIGHT TIN/LEAD ENTIRE STOCK OVER 1.27 μ m MIN NICKEL ENTIRE STOCK.
- \triangle 0.38 μ m MIN GOLD IN LOCALIZED GOLD PLATE AREA, 2.5 μ m MIN BRIGHT TIN/LEAD IN LOCALIZED TIN/LEAD PLATE AREA, BOTH OVER 1.27 µm MIN NICKEL ON ENTIRE STOCK.
- Δ 0.76 μm MIN GOLD IN LOCALIZED GOLD PLATE AREA, 2.5 μm MIN BRIGHT TIN/LEAD IN LOCALIZED TIN/LEAD PLATE AREA, BOTH OVER 1.27 µm MIN NICKEL ON ENTIRE STOCK.
- 4. WIRE RANGE 20-24 AWG.

2

- 5. INSULATION RANGE 0.89-1.52
- 🙆 2.54 μm MIN BRIGHT TIN ENTIRE STOCK OVER 1.27 μm MIN NICKEL ENTIRE STOCK.
- \triangle 0.38 μ m MIN GOLD IN LOCALIZED GOLD PLATE AREA, 2.5 μ m MIN BRIGHT TIN IN LOCALIZED TIN PLATE AREA, BOTH OVER 1.27 µm MIN NICKEL ON ENTIRE STOCK.
- / 0.76 μm MIN GOLD IN LOCALIZED GOLD PLATE AREA, 2.5 μm MIN BRIGHT TIN IN LOCALIZED TIN PLATE AREA, BOTH OVER 1.27 µm MIN NICKEL ON ENTIRE STOCK.
- NOTE DELETED.
- TIN PLATING THICKNESS INSIDE WIRE AND INSULATION BARRELS TO BE I.27 µm MIN.

| I | ZED |
|---|-----------------|
| A | $\overline{78}$ |

| | | | - 794608 - | 2 | 8 | - 7 9 4 6 2 - 2 |
|-----------------------|---------------------------------|--|--------------------------------|---|---------------|----------------------------|
| | | | - 7 9 4 6 0 8 - | | 7 | - 7 9 4 6 2 - |
| | | | - 794608-0 | | 6 | - 7 9 4 6 2 - 0 |
| | SUPERSEDED BY I-794612-2 | | 794608-3 | | 3 | 7946+2-3- |
| | SUPERSEDED BY -7946 2- | | -794608-2 | | 2 | 7946+2-2- |
| | SUPERSEDED BY 1 - 794612 - 0 | | 794608-1 | | | 7946+2-+ |
| | REMARKS | | REELED Part numbi | ER | FINISH | LOOSE PIECE PART NUMBER |
| THIS DRAWING IS A CON | C | WN WJ HK WDA | 29AUG2000 RUDY 29AUG2000 | · · | € TE | TE Connectivity |
| | PLC ±- PLC ±- PLC ±0.13 | APVD 29AUG200 W DAVIS PRODUCT SPEC 08 - 836 APPLICATION SPEC | | D NAME PLUG CONTACT, CRIMP SNAP, 20-24 A LOOSE PIECE, MICRO MATE-N-LOK(TM - | | |
| AN- MATERIAL FI | PLC ±- GLES ±- NISH W | - 3000 si | 200 | $\begin{array}{c c} \text{ge code} & \text{drawing no} \\ \hline 779 & \text{C} = 7946 \end{array}$ | RESTRICTED TO | |
| 0.20 THK - brass - | | | CUSTOMER DRAWING | | | LE O : I SHEET OF I REV D |