THIS DRAWING IS A CONTROLLED DOCUMENT.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	E	ECR−23−170423, Annotation Update	27MAR2023	H.M	S.S

-1: AS SHOWN

注記

1．本製品は圧着用クリンパの耐摩耗性を向上させるために使用する潤滑オイルである.

2．製造メ-カ-/メ-カ-型番

メ-カ-：STONER INC. (USA)

メ-カ-型番：E807

3．STONER社発行のSDS (Safety Data Sheet)は２枚目以降を参照ください.

最新版のSDSについてはSTONER社へお問い合わせ願います.

4．外形寸法と重量



重量：約510g

WEIGHT：APPROX. 510g

毒物及び劇物取締法　：非該当

労働安全衛生法　：非該当

PRTR法　：非該当

© TE Connectivity. All Rights Reserved.

DIMENSIONS: mm	DWN K.ISHIZUKA 28MAR2003	MATERIAL COML	FINISH −
TOLERANCES UNLESS OTHERWISE SPECIFIED:	CHK K.ISHIZUKA 28MAR2003	TE Connectivity Ltd.	
0 PLC ± −	APVD S.YABE 28MAR2003		
1 PLC ± −	PRODUCT SPEC —	NAME CRIMPER LUBRICANT クリンパ ルブリカント	
2 PLC ± −			
3 PLC ± −	APPLICATION SPEC —	SIZE A4 / CAGE CODE 00779 / DRAWING NO C−939691	RESTRICTED TO —
4 PLC ± −			
ANGLES ± −	WEIGHT 510		
	CUSTOMER DRAWING	SCALE 1:1 / SHEET 1 OF 7	REV E

1469−35 (1/15)

THIS DRAWING IS A CONTROLLED DOCUMENT.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	—	—

Safety Data Sheet
E807 Terminal Lubricant

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated
1070 Robert Fulton Hwy.
Quarryville, PA 17566
1-800-227-5538

Product Name:	Terminal Lubricant
Product Code:	E807
Product Use:	Lubricant
24-hour emergency phone:	1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols

GHS Classification	Skin Sensitisation Category 1
Signal Word	Warning
Hazard Statements	May cause an allergic skin reaction.
Precautionary Statements	
Prevention	Avoid breathing dust/fume/gas/mist/vapours/spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.
Response	P302+P352 - If on skin: Wash with plenty of soap and water. P321 - Specific treatment (see on this SDS). If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT	CAS #	Percent
Sebacate oil	122-62-3	80 - 100

HMIS® III* HAZARDOUS WARNINGS:

Health: 1 Flammability: 1 Physical: 0 Personal Protective Equipment: See Section 8

* See www.paint.org/hmis or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
Skin Contact:	In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse.
Ingestion:	Contact a physician, medical facility, or poison control center for advice on whether to induce vomiting. No harmful effects expected.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

NOTES TO PHYSICIAN:
No additional first aid information available.

© TE Connectivity. All Rights Reserved.

DIMENSIONS: mm	DWN K.ISHIZUKA 28MAR2003	MATERIAL COML	FINISH –
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± – 1 PLC ± – 2 PLC ± – 3 PLC ± – 4 PLC ± – ANGLES ± –	CHK K.ISHIZUKA 28MAR2003	TE Connectivity Ltd.	
	APVD S.YABE 28MAR2003	NAME CRIMPER LUBRICANT クリンパ ルブリカント	
	PRODUCT SPEC —	SIZE A4 / CAGE CODE 00779	DRAWING NO C-939691 / RESTRICTED TO —
	APPLICATION SPEC —		
	WEIGHT —	CUSTOMER DRAWING	SCALE 1:1 / SHEET 2 OF 7 / REV E

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	—	—

5. FIRE FIGHTING MEASURES

Fire Fighting Instructions: Use water spray, foam, dry chemical, or CO2. Fire fighters should wear normal protective equipment and positive-pressure self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:
Wear appropriate personal protective equipment (PPE). Avoid run-offinto storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling: Avoid prolonged or repeated contact with skin.
Storage: Keep container tightly closed when not in use. Store in a cool, dry, well ventilated area away from all sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects).
Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.
Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.
Respiratory Protection: No respiratory protection required under normal conditions of use.

COMPONENT	CAS #	ACGIH TLV	OSHA PEL	OTHER
Sebacate oil	122-62-3	5 mg/m3 TWA	Not established	Not established

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Bulk liquid	Lower Flammability Limit (%):	Not applicable
Appearance:	Light yellow	Upper Flammability Limit (%):	Not applicable
Odor:	Characteristic	Vapor Pressure (PSIG @ 70°F):	No data available
Odor Threshold:	Mild	Vapor Density [air = 1]:	0.000000
pH:	Not applicable	Relative Density (H2O=1):	0.92
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Not determined
Boiling Point (°F):	No data available	Partial Coefficient: n-octanol/water:	No data available
Flash Point (°F PMCC):	425	Autoignition Temperature (°F):	Not applicable
Evaporation Rate:	Not determined	Decomposition Temperature (°F):	No data available
Flammability (solid, gas):	No data available	Viscosity, dynamic (cSt):	12.5 cSt
Percent VOCs (%):	< 0.0001		

10. STABILITY AND REACTION

Chemical Stability: Stable.
Conditions to Avoid: Avoid contact with: Strong oxidizing agents.
Decomposition Products: Burning can produce the following combustion products: Carbon dioxide and carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Dermal Toxicity: Dermal LD50 Rabbit = 9400 mg/kg
Inhalation Toxicity: Inhalation LC50 Rat = 200 mg/kg
Oral Toxicity: Oral LD50 Rat 2000 mg/kg
Reproductive & Developmental Toxicity: No data available.
IARC Carcinogen Designation: No data available

Ingredient	CAS #	Toxicological Data
No data available		

12. ECOLOGICAL INFORMATION

Ecological Toxicity: No data available
Mobility: No data available

Ingredient	CAS #	Toxicological Data
No data available		

13. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

© TE Connectivity. All Rights Reserved.

DIMENSIONS: mm	DWN K.ISHIZUKA 28MAR2003	MATERIAL COML	FINISH –
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± – ; 1 PLC ± – ; 2 PLC ± – ; 3 PLC ± – ; 4 PLC ± – ; ANGLES ± –	CHK K.ISHIZUKA 28MAR2003	TE Connectivity Ltd.	
	APVD S.YABE 28MAR2003	NAME CRIMPER LUBRICANT クリンパ ルブリカント	
	PRODUCT SPEC —	SIZE A4 / CAGE CODE 00779	DRAWING NO C-939691 / RESTRICTED TO —
	APPLICATION SPEC —		
	WEIGHT —	CUSTOMER DRAWING	SCALE 1:1 / SHEET 3 OF 7 / REV E

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	–	–

14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT		Not regulated by agency		
IATA		Not regulated by agency		
IMDG		Not regulated by agency		

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			SARA Section 313

Toxic Substances Control Act
All components of this product are listed on the TSCA inventory.

California Prop 65
This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.

16. OTHER INFORMATION

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 04/05/18

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.

© TE Connectivity. All Rights Reserved.

DIMENSIONS: mm	DWN K.ISHIZUKA 28MAR2003	MATERIAL COML	FINISH –
TOLERANCES UNLESS OTHERWISE SPECIFIED:	CHK K.ISHIZUKA 28MAR2003	TE Connectivity Ltd.	
0 PLC ± –	APVD S.YABE 28MAR2003		
1 PLC ± –	PRODUCT SPEC –	NAME CRIMPER LUBRICANT クリンパ ルブリカント	
2 PLC ± –			
3 PLC ± –	APPLICATION SPEC –	SIZE A4 / CAGE CODE 00779 / DRAWING NO C-939691	RESTRICTED TO –
4 PLC ± –			
ANGLES ± –	WEIGHT –		
CUSTOMER DRAWING		SCALE 1:1 / SHEET 4 OF 7	REV E

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	–	–

以下は、「Stoner社 E807 に関するSDS」の日本語訳です。参考として閲覧ください。

安全データシート (SDS)

E807 ターミナル潤滑油

Stoner

株式会社ストーナーの製品を正しくご使用いただくために、本情報のコピーおよびダウンロードを許可する。
(1) Stoner Inc.の事前の同意がない限り、この情報を変更せずに完全にコピーすること。
(2) コピーやオリジナルを、利益を得る目的で再販売または配布しないこと。

1. 識別

Stoner Incorporated
1070 Robert Fulton Hwy
Quarryville, PA 17566
1-800-227-5538

製品:	E807 ターミナル潤滑油
製品番号:	E807
主な用途:	金属の滑走および離型
24 時間緊急電話番号:	1-800-424-9300 [CHEMTREC]

2. ハザードの識別(危険有害性の要約)

潜在的な健康への影響
1910.1200 項の(d)に従った化学物質の分類。。

GHS ハザード シンボル

GHS 分類	皮膚感作性区分 1
注意喚起語	警告
危険有害性情報	アレルギー性皮膚反応を引き起こす可能性。
注意事項	
安全対策	粉塵／煙／ガス／ミスト／蒸気／スプレーを吸入しないこと。 汚染された作業衣は作業場から出してはならない。 保護手袋/保護衣/保護眼鏡/保護面を着用すること。
応急措置	P302+P352 – 皮膚に付着した場合: 多量の石鹸と水で洗い流すこと。 P321 – 特別な処置 (本 SDS に記載)。 皮膚刺激または発疹が生じた場合: 医師の診断/手当てを受けること。 汚染された衣類は、再使用する前に洗濯すること。
廃棄	内容物／容器は、地域／国／国際的な有害廃棄物規則に従って廃棄すること。

3. 組成・成分情報

コンポーネント	CAS 番号	パーセント
セバケート油	122-62-3	80 – 100

HMIS® III*による警告

健康: 1	可燃性: 1	物理: 0	保護措置:8 を参照

* 評価システムの詳細については、www.paint.org/hmis を参照するか、ACA (1 (202) 462-6272) に確認する。

4. 応急措置

目に入った場合	まぶたを広げたまま、すぐに多量の水で少なくとも 15 分間、やさしく洗眼すること。 症状が続く場合、または視覚障害がある場合は、医師の診察を受けること。

© TE Connectivity. All Rights Reserved.

DIMENSIONS: mm	DWN K.ISHIZUKA 28MAR2003	MATERIAL COML	FINISH –
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± – 1 PLC ± – 2 PLC ± – 3 PLC ± – 4 PLC ± – ANGLES ± –	CHK K.ISHIZUKA 28MAR2003	TE Connectivity Ltd.	
	APVD S.YABE 28MAR2003	NAME CRIMPER LUBRICANT クリンパ ルブリカント	
	PRODUCT SPEC –	SIZE A4 / CAGE CODE 00779 / DRAWING NO C-939691	RESTRICTED TO –
	APPLICATION SPEC –		
	WEIGHT –	CUSTOMER DRAWING / SCALE 1:1 / SHEET 5 OF 7	REV E

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	—	—

皮膚に付着した場合	接触した場合は、汚染された部分を直ちに多量の水で少なくとも 15 分間洗浄すること。症状が続く場合は医師の診察を受けること。衣類は再使用する前に洗濯すること。
飲み込んだ場合	医師、医療施設、または毒物管理センターに連絡して、嘔吐を誘発するかどうかについて助言を求める。有害な影響は予想されない。
吸入	新鮮な空気の場所に移す。呼吸がない場合は人工呼吸を行う。呼吸が困難な場合は、酸素を与える。
医師への注意	利用可能な追加の応急処置情報無し。

5. 火災時の措置

消火方法	水スプレー、泡、乾燥化学薬品、または CO2 を使用すること。消火を行う者は通常の保護具と陽圧自給式呼吸器を着用すること。

6. 漏出時の措置

材料が放出またはこぼれた場合の手順
適切な個人用保護具(PPE)を着用すること。自然の水路につながる雨水管や溝に流出しないようにすること。吸収性物質で清掃すること。吸引性物質は容器に入れ密栓する。容器は適切に処理する。

7. 取扱い及び保管上の措置

取扱い上の注意	皮膚への長時間または繰り返しの接触を避ける。
保管上の注意	使用しないときは、容器を密閉して保管する。 すべての着火源から離れた、涼しく乾燥した換気の良い場所に保管する。

8. 暴露防止及び保護措置

工学的管理	換気は、SDS のこのセクションで以下に示されている制限を超えて、既知の、疑わしい、または明らかな悪影響からの曝露を防ぐために適切である必要がある。
目の保護	本製品を取り扱う際には、サイドシールド付きの耐薬品性安全眼鏡を着用すること。液体の飛沫や噴霧、空気中の物質と眼が接触する可能性がある場合は、化学スプラッシュゴーグルや顔面シールドなどの眼保護具を着用すること。洗眼器を用意すること。
皮膚の保護	長時間または繰り返し皮膚に接触する可能性がある場合は、耐薬品性手袋を使用すること。
呼吸保護:	通常の使用条件下では、呼吸保護の必要無し。

コンポーネント	CAS 番号	ACGIH TLV	OSHA PEL	その他
セバケート油	122-62-3	5 mg/m3 TWA	確立されていない	確立されていない

9. 物理的および化学的性質

物理的状態	バルク液体	燃焼性下限 (%)	該当なし
外観	薄黄色	燃焼性上限 (%)	該当なし
臭気	特徴	蒸気圧(PSIG @70° F)	データなし
臭気の閾値	軽度	蒸気密度 [空気 = 1]	0.000000
pH	該当なし	相対密度 (H2O=1)	0.92
融点/凝固点 (° F)	データなし	水への溶解度	データなし
沸点 (° F)	データなし	部分係数: n オクタノール/水:	データなし
引火点 (° F PMCC)	425	自然発火温度 (° F)	該当なし
蒸発率	決まっていない	分解温度 (° F)	データなし
可燃性 (固体、気体)	データなし	粘度、動的 (cSt):	12.5 cSt

© TE Connectivity. All Rights Reserved.

DIMENSIONS: mm	DWN K.ISHIZUKA 28MAR2003	MATERIAL COML	FINISH –
TOLERANCES UNLESS OTHERWISE SPECIFIED:	CHK K.ISHIZUKA 28MAR2003	TE Connectivity Ltd.	
0 PLC ± –	APVD S.YABE 28MAR2003		
1 PLC ± –	PRODUCT SPEC —	NAME CRIMPER LUBRICANT	
2 PLC ± –			
3 PLC ± –	APPLICATION SPEC —	SIZE A4 / CAGE CODE 00779 / DRAWING NO C-939691	RESTRICTED TO —
4 PLC ± –			
ANGLES ± –	WEIGHT —		
CUSTOMER DRAWING		SCALE 1:1 / SHEET 6 OF 7	REV E

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	–	–

10. 安定性及び反応性

化学的安定性　安定
避けるべき条件　以下との接触を避ける　強力な酸化剤。
分解生成物　燃焼により、次の燃焼生成物が生成される可能性。二酸化炭素と一酸化炭素。

11. 有毒性情報

皮膚毒性　皮膚 LD50 Rabbit = 9400 mg/kg
吸入毒性　吸入 LC50 Rat = 200 mg/kg
経口毒性　経口 LD50 Rat 2000 mg/kg
生殖・発生毒性　データなし
IARC 発がん性物質指定　データなし

成分	CAS 番号	毒性データ
データなし		

12. 環境影響情報

生態毒性　データなし
可動性　データなし

成分	CAS 番号	毒性データ
データなし		

13. 廃棄上の注意

廃棄　国、県、および各自治体の条例に従って廃棄すること。

14. 輸送に関する情報

機関	識別番号	正式な輸送名	危険物分類	包装グループ
DOT		機関による規制なし		
IATA		機関による規制なし		
IMDG		機関による規制なし		

15. 規制情報

警告: 本製品は、以下の規制機関の報告義務のある化学物質を含んでいます。

コンポーネント	CAS 番号	重量%	規制機関
このセクションに記載されているコンポーネント無し。			SARA Section 313

TSCA 状況
本製品のすべてのコンポーネントは、TSCA 目録にリストされている。

カリフォルニア プロップ 65
この製品には、がん、先天性欠損症、またはその他の生殖障害を引き起こすカリフォルニア州プロポジション 65 の成分は含まれていない。

16. その他の情報

その他の情報:　作成者 L. Dean Swartz、SDS コーディネーター

バージョン日付:　04/05/18

この SDS に含まれる情報は、バージョン日付の時点では正確であると考えられるが、それを保証するものではない。この情報の使用および本製品の使用条件は、ストーナー社の管理外であるため、安全に使用するための条件を決定するのは使用者の義務である。

© TE Connectivity. All Rights Reserved.

DIMENSIONS: mm	DWN K.ISHIZUKA 28MAR2003	MATERIAL COML	FINISH –
TOLERANCES UNLESS OTHERWISE SPECIFIED:	CHK K.ISHIZUKA 28MAR2003	TE Connectivity Ltd.	
0 PLC ± –	APVD S.YABE 28MAR2003		
1 PLC ± –	PRODUCT SPEC –	NAME CRIMPER LUBRICANT	
2 PLC ± –			
3 PLC ± –	APPLICATION SPEC –	SIZE A4 / CAGE CODE 00779 / DRAWING NO C-939691	RESTRICTED TO –
4 PLC ± –			
ANGLES ± –	WEIGHT –		
CUSTOMER DRAWING		SCALE 1:1 / SHEET 7 OF 7	REV E