

# **Engineering Product Design**

**Product Construction** 7 Conductor Cable Shielded and Jacketed

**Controlled Customer Copy** B.W.B. **GERMANY** 

**Product Description** 

Rev

VG 95218 T028 C046


2

**Designer** Paul Cleary **Date** 20/08/2019 **Product Manager** Mark Johnstone

**Date** 20/08/2019

# **Component Identification**

### **Cross-Section**



# Components

ID Type	Quantity	Part Description (Components refer to issue in effect at date of issue of this EPD)	
A Wire	7	VG 95218-T020-E089	

## **Component Identification**

Key	Wire/Core Colour(s)	Wire/Core Number(s)	Jacket/Wrap Colour(s)	Jacket/Wrap Number
A1	9	1		
A2	9	2		
A3	9	3		
A4	9	4		
A5	9	5		
A6	9	6		
A7	9	7		

# Cabling

Layer No	Quantity	Description	Nominal O.D. mm
Layer 1	1	VG 95218-T020-E089	
Layer 2	6	VG 95218-T020-E089	6.2

Tyco Electronics UK Ltd. Faraday Road, Dorcan Swindon SN3 5HH Tel: (01793) 528171 Website: www.te.com

TE Connectivity is a trading name of Tyco Electronics UK Ltd, which is registered in England and Wales, number 550926. Registered office: Faraday Road, Dorcan, Swindon, SN3 5HH

This drawing and the information set forth hereon are the property of Tyco Electronics UK Ltd, and are to be held in trust and confidence. Publication, duplication, disclosure or use for any purpose not expressly authorised in writing by Tyco Electronics UK Ltd is prohibited.

© 2019 Tyco Electronics UK Limited. A TE Connectivity Ltd company. All Rights Reserved.



# **Engineering Product Design**

Product Construction
7 Conductor Cable
Shielded and Jacketed

Controlled Customer Copy B.W.B. GERMANY Product Description

Rev

2

VG 95218 T028 C046

-	-	
r	111	Or
v	uι	CI

Layer Type	Description	Nominal O.D. mm
Wrap:	Polyester	6.3
Shield: Optimised Braid	Tin Plated Copper	6.9
Jacket: Extrusion 1	Zerohal® - Black Marked 'Raychem - VG 95218 T028 C046 - K1010 - VDE Reg.Nr. 7095 - LMGSGO - (7x1,5)'	8.6 ±0.4 Min Wall - 0.70mm

#### **Cable Characteristics**

Calculated Maximum Weight	196 (kg/km)	
Maximum Surface Transfer Impedance	70 milli Ohms/metre @ 30MHz 30 milli Ohms/metre @ 10MHz	
This cable is RoHS Compliant		

### **Specifications**

VG 95218 Part 28 Type C

#### **Notes**

Braid - AWG36 Internal reference - EPD93657B

# Lengths

Unless otherwise specified on your order this cable may be supplied in the following maximum number of continuous lengths with no single length less than 25m:

Order Quantity (m) + One other length 100