# 1-2236888-2 ACTIVE

#### HSD

TE Internal #: 1-2236888-2

Data Connectivity Housings, Housing for Female Terminals, B, Wireto-Device, 8 Position, .5 in [12.7 mm] Centerline, Crimp, Cable Type

SSQ, HSD

View on TE.com >



Connectors > Automotive Connectors > Data Connectivity Systems > Data Connectivity Housings











Connector & Housing Type: Housing for Female Terminals

Mating Pin Diameter: .6 mm [ .024 in ]

Connector & Keying Code: **B**Connector System: **Wire-to-Device** 

Number of Positions: 8

#### **Features**

### **Product Type Features**

Mixed & Hybrid Connector	No
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Device
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Snap-Lock	With
Number of Positions	8
Electrical Characteristics	
Impedance	100 Ω
Body Features	
Cable Exit Type	Fixed
Ferrule	Without

PBT GF

**Body Material** 



Connector & Keying Code	В	
Contact Features		
Center Contact	Without	
Contact Type	Socket	
Contact Mating Area Plating Material	Unplated	
RF Connector Center Contact Plating Material	None	
Mating Pin Diameter	.6 mm[.024 in]	
Termination Features		
Termination Method to Wire & Cable	Crimp	
Mechanical Attachment		
Panel Attachment Style	Rear Mount	
Mating Retention	With	
Housing Features		
Housing Color	White	
Centerline (Pitch)	12.7 mm[.5 in]	
Jsage Conditions		
Cable Type	SSQ	
Operation/Application		
Shielded	No	
Circuit Application	Signal	
ndustry Standards		
IP Rating	IPX9K	
Packaging Features		
Packaging Method	Box & Carton	
Other		
Outer Contact Plating Material	None	

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant	
------------------------------	-----------	--



EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**



# Also in the Series | HSD







### Customers Also Bought





















### **Documents**

#### **Product Drawings**

DUAL HSD 12.7MM,SOC HSG,90DEG,COD B

English

### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_1-2236888-2\_B.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-2236888-2\_B.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-2236888-2\_B.3d\_igs.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Data Connectivity Housings, Housing for Female Terminals, B, Wire-to-Device, 8 Position, .5 in [12.7 mm] Centerline, Crimp, Cable Type SSQ, HSD

