# PR4



TE Connectivity has acquired the DIN Rail Terminal Block product range from ABB

Products + Low Voltage Products and Systems + Connection Devices + Terminal Blocks Accessories

→ Mounting Rails

**General Information** 

Extended Product Type: PR4

**Product ID:** 1SNA168500R1200 **EAN:** 3472591685008

Catalog Description: PR4 Symmetrical mounting rail complying with IEC60715

Long Description: - Symmetrical mounting rail complying with IEC60715, - The rigidity of the r

ail is maximised by the 2.3 mm 0.090 in thickness of the rail, and by its soli d, non slotted construction, - PR4 TH 35-15 is the most rigid mounting rail

solution and it can suppo

Ordering

Minimum Order Quantity: 2 piece

Customs Tariff Number: 72166110

Popular Downloads

Data Sheet, Technical Information: 1SNK160041D0201

**Dimensions** 

Product Net Width: 2000 mm

Product Net Height: 35 mm

Product Net Length: 15 mm

Product Net Depth / Length: 15 mm

Product Net Weight: 915 g

Technical

Rated Cross-Section: 50 mm<sup>2</sup>

Spacing: 2000 mm

Function: Mounting Rail

Rated Short-time Withstand for 1 s 6000 A

Current (I<sub>cw</sub>):

Insulation Material: Zinc plating and passivation steel

Mounting on DIN Rail: TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715

Suitable For: BAM4

D1.5/4.2L D1.5/4.2L.2L

D1.5/4.4L D10/10.1.2L

D10/10.1.21

D10/10.3L

D10/10.NT.L

D16/12.2L

D16/12.3L

D16/12.NT.L

D2.5/5.2L

D2.5/5.2L.2L

DZ.0/0.ZL.ZL

D2.5/5.3L

D2.5/5.4L

D2.5/5.A.L.L

D2.5/5.A.LL.L

D2.5/5.A.LLP.L

D2.5/5.A.N.L

D2.5/5.A.NL.L

D2.5/5.A.NLP.L

D2.5/5.A.NTLP.

### Technical UL/CSA

Connecting Capacity UL/CSA: Stranded 0 AWG

## Certificates and Declarations (Document Number)

RoHS Information: 1SND230012F0203

## Classifications

Object Classification Code: X

ETIM 4: EC001285 - Mounting rail

ETIM 5: EC001285 - Mounting rail

ETIM 6: EC001285 - Mounting rail

### **Container Information**

Package Level 1 Units: 2 piece

Package Level 1 Gross Weight: 1.83 kg

Package Level 1 EAN: 3472591685008

Product Packing Type: Rail

