## D2.5/8.SNNT.ADO2



TE Connectivity has acquired the DIN Rail Terminal Block product range from ABB

Products + Low Voltage Products and Systems + Connection Devices + Terminal Blocks + Solution Series

General Information

 Extended Product Type:
 D2.5/8.SNNT.ADO2

 Product ID:
 1SNA199186R1300

 EAN:
 3472591991864

Catalog Description: D2.5/8.SNNT.ADO2 IDC Terminal Blocks - Disconnect - with test socket A

DO - ADO - Grey, Blue

Long Description: - Disconnect terminal blocks aligned with fuse holder terminal blocks, - Wit

h the ABB ADO System®, experience the fastest and most reliable connect ion on the market, - Designed for control applications exposed to severe constrains (vibrations, shocks, corrosion etc.), - Up to 2 wires per connection.

Ordering

Color: Grey, Blue

Minimum Order Quantity: 50 piece

Customs Tariff Number: 85369010

Popular Downloads

Data Sheet, Technical Information: 1SNC160020C0201

Instructions and Manuals: 1SNC160020C0201

**Dimensions** 

Product Net Width: 8 mm

Product Net Height: 80.5 mm

Product Net Depth / Length: 41 mm

Product Net Weight: 18 g

**Technical** 

Rated Cross-Section: 2.5 mm<sup>2</sup>

Spacing: 8 mm

Connection Type: ADO System

Function: Disconnect

Number of Levels: 1

Rated Current (I<sub>n</sub>): Main Circuit 10 A

Rated Short-time Withstand for 1 s 300 A

Current (Icw):

Rated Voltage (U<sub>r</sub>): 630 V

Rated Impulse Withstand Voltage $(U_{imp})$ :	8000 V
Dielectric Test Voltage:	2500 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
echnical UL/CSA	
Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
Connecting Capacity UL/CSA:	Stranded 14 AWG
Flammability According to UL94:	V0
Environmental	
Ambient Air Temperature:	Operation -55 +110 °C Storage -55 +110 °C
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Certificates and Declarations (I	Document Number)
cUL Certificate:	1SND163001A0202
Declaration of Conformity - CE:	1SND225052U1000
EAC Certificate:	1SND162001A1100
Environmental Information:	1SND220024E1002
Instructions and Manuals:	1SNC160020C0201
RoHS Information:	1SND230472F0201
Classifications	
Object Classification Code:	X
ETIM 4:	EC000902 - (Knife) disconnect terminal block
ETIM 5:	EC000902 - (Knife) disconnect terminal block
ETIM 6:	EC000902 - (Knife) disconnect terminal block

**Container Information** 

Package Level 1 Units:

Package Level 1 Width:

Package Level 1 Height:

Package Level 1 EAN:

Package Level 1 Depth / Length:

Package Level 1 Gross Weight:

50 piece

176 mm

200 mm

75 mm

0.9 kg

3472591991864

Package Level 2 Units:	450 piece
Package Level 2 Width:	300 mm
Package Level 2 Depth / Length:	500 mm
Package Level 2 Height:	300 mm
Package Level 2 Gross Weight:	8.6 kg
Package Level 3 Units:	10800 piece
Product Packing Type:	Box

