# DH2.5/5.2L



TE Connectivity has acquired the DIN Rail Terminal Block product range from ABB

Products + Low Voltage Products and Systems + Connection Devices + Terminal Blocks + Solution Series

#### **General Information**

Extended Product Type: DH2.5/5.2L

Product ID: 1SNA290261R1400 EAN: 3472592902616

Catalog Description: DH2.5/5.2L Spring Terminal Blocks - Miniblocks - Grey

Long Description: - Save space with compact angled terminal blocks, - Easy base mounting t

hanks to snap in mounting foot, - Clamping contact pressure non depende

nt on the operator and automatic creeping compensation.

## Ordering

Color:	Grey
Minimum Order Quantity:	100 piece
Customs Tariff Number:	85369010

## Popular Downloads

Data Sheet, Technical Information:	1SNC160020C0201
Instructions and Manuals:	1SNC160020C0201

#### **Dimensions**

Product Net Width:	5 mm
Product Net Height:	33 mm
Product Net Depth / Length:	24.5 mm
Product Net Weight:	4 g

#### **Technical**

Rated Cross-Section:	2.5 mm²
Spacing:	5 mm
Connection Type:	Spring
Function:	Miniblock
Number of Levels:	1
Connecting Capacity Main Circuit:	Spring Clamp / Flexible 1x 0.12 2.5 mm <sup>2</sup> Spring Clamp / Rigid 1x 0.12 4 mm <sup>2</sup> Spring Clamp / With Insulated Ferrrule 1x 0.5 1.5 mm <sup>2</sup>
Gauge Type:	A2
Rated Current (I <sub>n</sub> ):	Main Circuit 24 A
Rated Short-time Withstand Current (I <sub>cw</sub> ):	for 1 s 300 A

Rated Voltage (U <sub>r</sub> ):	800 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> ):	8000 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Wire Stripping Length:	9.5 mm
Recommended Screw Driver:	3.5 mm

#### Technical UL/CSA

Maximum	Operating	Voltage

Main Circuit 600 V

UL/CSA:

**Connecting Capacity Main Circuit** 

UL/CSA:

Spring Clamp / Flexible 1x 26 ... 12 AWG Spring Clamp / Rigid 1x 26 ... 12 AWG

Connecting Capacity UL/CSA: Stranded 12 AWG

Flammability According to UL94: V0

#### Environmental

Ambient Air Temperature: Operation -55 ... +110 °C

Storage -55 ... +110 °C

RoHS Status: Following EU Directive 2002/95/EC August 18, 2005 and amendment

### Certificates and Declarations (Document Number)

cUL Certificate:	1SND162000A0204
Declaration of Conformity - CE:	1SND225022U1000
EAC Certificate:	1SND162001A1100
Environmental Information:	1SND220031E1002
Instructions and Manuals:	1SNC160020C0201
RMRS Certificate:	1SND162000A1101
RoHS Information:	1SND230488F0201

#### Classifications

Object Classification Code:	X
ETIM 4:	EC000897 - Feed-through terminal block
ETIM 5:	EC000897 - Feed-through terminal block
ETIM 6:	EC000897 - Feed-through terminal block

#### **Container Information**

Package Level 1 Units:	100 piece
Package Level 1 Width:	101 mm
Package Level 1 Depth / Length:	220 mm

Package Level 1 Height:	47 mm
Package Level 1 Gross Weight:	0.4 kg
Package Level 1 EAN:	3472592902616
Package Level 2 Units:	1000 piece
Package Level 2 Width:	300 mm
Package Level 2 Depth / Length:	500 mm
Package Level 2 Height:	150 mm
Package Level 2 Gross Weight:	4.35 kg
Package Level 3 Units:	48000 piece
Product Packing Type:	Box

