

C16/12.N



TE Connectivity has acquired the DIN Rail Terminal Block product range from ABB

Products → Low Voltage Products and Systems → Connection Devices → Terminal Blocks → SNACompact Series

General Information

Extended Product Type:	C16/12.N
Product ID:	1SNL512020R0000
EAN:	3472599857438
Catalog Description:	C16/12.N
Long Description:	- 16 mm ² Feed-through terminal with ABB patented screw Clamp Connection

Ordering

Color:	Blue
Minimum Order Quantity:	50 piece
Customs Tariff Number:	85369010

Popular Downloads

Data Sheet, Technical Information:	1SNC160028L0202
Instructions and Manuals:	1SNC160028L0202

Dimensions

Product Net Width:	12 mm
Product Net Height:	45.5 mm
Product Net Depth / Length:	48 mm
Product Net Weight:	18 g

Technical

Rated Cross-Section:	16 mm ²
Spacing:	12 mm
Connection Type:	Screw clamp
Function:	Feed-through
Connecting Capacity Main Circuit:	Screw Clamp / Flexible 1x 0.5 ... 16 mm ² Screw Clamp / Flexible 2x 0.5 ... 10 mm ² Screw Clamp / Rigid 1x 0.5 ... 16 mm ² Screw Clamp / Rigid 2x 0.5 ... 10 mm ² Screw Clamp / With Insulated Ferrule 1x 0.5 ... 16 mm ² Screw Clamp / Without Insulated Ferrule 1x 0.5 ... 16 mm ² Screw Clamp / With Twin Ferrule 2x 0.5 ... 10 mm ²
Gauge Type:	B6
Rated Current (I_n):	Main Circuit 76 A

Rated Short-time Withstand Current (I_{cw}):	for 1 s 1920 A
Rated Voltage (U_r):	1000 V
Rated Impulse Withstand Voltage (U_{imp}):	8000 V
Dielectric Test Voltage:	2000 V
Pollution Degree:	3
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Insulation Material:	Polyamide
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Wire Stripping Length:	12.0 mm
Tightening Torque:	acc. IEC 60947-1 1.2 N·m Manufacturer 1.4 N·m

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Rigid 1x 20 ... 4 AWG Screw Clamp / Rigid 2x 20 ... 8 AWG Screw Clamp / With Insulated Ferrule 1x 20 ... 6 AWG Screw Clamp / Without Insulated Ferrule 1x 20 ... 4 AWG Screw Clamp / With Twin Ferrule 2x 20 ... 10 AWG
Flammability According to UL94:	V0

Environmental

Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Certificates and Declarations (Document Number)

cUL Certificate:	1SND161106A0201
Declaration of Conformity - CE:	1SND225041U1000
EAC Certificate:	1SND161009A1100
Instructions and Manuals:	1SNC160028L0202
RoHS Information:	1SND230544F0201

Classifications

Object Classification Code:	X
ETIM 4:	EC000897 - Feed-through terminal block
ETIM 5:	EC000897 - Feed-through terminal block
ETIM 6:	EC000897 - Feed-through terminal block

Container Information

Package Level 1 Units: 50 piece

Package Level 1 Width: 122 mm

Package Level 1 Depth / Length: 224 mm

Package Level 1 Height: 47 mm

Package Level 1 Gross Weight: 0.9 kg

Package Level 1 EAN: 3472599857438

Package Level 2 Units: 450 piece

Package Level 2 Width: 250 mm

Package Level 2 Depth / Length: 330 mm

Package Level 2 Height: 210 mm

Package Level 2 Gross Weight: 8.1 kg

Product Packing Type: Box

