



B1322W

Wide Band Mobile Load Coil Antenna 132-174 MHz

Laird Connectivity's ongoing commitment to refinement in mechanical and electrical design has resulted in the most technically advanced mobile load coil antennas on the market. Exclusive features such as stainless-steel whips, housings constructed with ABS material injected molded around a solid brass insert, and gold-plated push pin contacts make Laird the obvious choice for quality and long-lasting value for demanding mobile radio communications.

FEATURES AND BENEFITS

- High performance wide-band mobile antenna
- Special UV-treated radome, resists sun damage
- Easy installation with optional NMO mounts
- 100% tested on a network analyzer
- Field tunable to your specific frequency requirement
- (cutting chart comes with the antenna)
- 1/2 wave design for both ground plane and no ground plane installations

APPLICATIONS

- Public safety
- Transportation
- Utility
- Military mode

ELECTRICAL SPECIFICATION

Operating Frequency (MHz)	132-174 (field-tunable)
VSWR	<2.0:1
Gain (dBi)	2.4
Bandwidth (MHz)	23
Pattern	Omnidirectional
Nominal Impedance (Ohms)	50
Max Power - Ambient 25°C (W)	100
Polarization	Vertical

ENVIRONMENTAL SPECIFICATIONS

Wind Survival - km/hr (mph)	161 (100)
Material Substance Compliance	RoHS

MECHANICAL SPECIFICATIONS

Whip length at 132 MHz – cm (inches)	- 102 (40)
Diameter – mm (inches)	36.7 (1.45)
Weight – kg (lbs.)	0.44 (1.2)
Mounting Options	NMO Mountable, Ground plane & No Ground Plane surfaces
Radiator Material	0.125" diameter, 17-7PH stainless steel whip
Spring Material (spring models only)	Stainless steel tempered spring
Base housing material	Chrome-plated brass top and bottom bushings with injection molded ABS plastic
Lightning Protection	-


CONFIGURATION

PART NUMBER	DESCRIPTION	CONNECTOR
B1322W	B-coil wide-band antenna (chrome)	1 1/8" 18 thread (NMO) mountable
BB1322W	B-coil wide-band antenna (black)	1 1/8" 18 thread (NMO) mountable
B1322WS	B-coil wide-band antenna (chrome) w/ spring	1 1/8" 18 thread (NMO) mountable
BB1322WS	B-coil wide-band antenna (black) w/ spring	1 1/8" 18 thread (NMO) mountable


RADIATION PATTERNS

132 MHz

Azimuth




Elevation




RADIATION PATTERNS

153 MHz

Azimuth




Elevation




174 MHz

Azimuth



Elevation



TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE, and TE connectivity (logo) are trademarks owned or licensed by the TE Connectivity Ltd. family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE Connectivity product is installed. Useful lifetime of the original end product may vary but is not warranted to exceed one (1) year from the original date of the end product purchase.

©2022 TE Connectivity. All Rights Reserved.

08/22 Original