

623 Plug

17-pin insulation insert Code 0° housing code 1 EMC - Shielding

A ST A 014 NN 00 40 0235 000 A S A 014 N 00 40 0235 000



Contact Arrangement mating view



number of pins temperature range clamping range protection type

Technical Data

Electrical Data rated current rated voltage rated insulation voltage (L-L)

signal max. 7 A* 125 V (AC/DC) 2000 V

-20 °C to 130 °C

Ø 9.0 mm to Ø 13.2 mm when connected IP 66/67

17

mating cycles

500

Data according to VDE 0110/EN61984, Paragraph 6.19.2.2 pollution degree 3

pollution degree over voltage category max. height for operation

2000 m

III

Material

housing insulation insert seals clamp ring zinc diecast / nickel plated PBT, UL 94 / V0 FKM brass / nickel plated

Contacts (not part of product contents)

Tools (not part of product contents)

© 2018 TE Connectivity

TE Connectivity, TE connectivity (logo), intercontec (logo) and speedtec are trademarks.

While TE Connectivity (TE) has made every reasonable effort to ensure the accuracy of the information in this presentation, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this article are for reference purposes only and are subject to change without notice. The the subject to change without for the consult TE for the

In this article are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

TE Connectivity Industrial GmbH Bernrieder Straße 15 94559 Niederwinkling, Deutschland Tel.: +49 9962 2002-0 Fax: +49 9962 2002-70 E-Mail: intercontec@te.com Web: www.intercontec.biz





Main Dimensions Plug *for max. wire cross-section pay attention to the cross-section of used contacts