



DSE 1810.01 AHZ

Variable Reluctance Speed Sensor

Product ID

Type #	Product #	Drawing #
DSE 1810.01 AHZ	304Z-03776	111039

General

Function

The DSE 1810.01 AHZ series variable reluctance (VR) speed sensors consist of an iron core, an inductive coil, and a permanent magnet. A ferrous pole wheel passing the sensor face changes the magnetic field strength, resulting in an AC voltage being induced in the coil. The frequency of the output signal is proportional to the speed of the moving target. The amplitude of the signal depends on speed, air gap, geometry of target, magnetic properties of target material, and the electrical load. VR sensors, also known as passive or electromagnetic sensors, do not require an external supply.

Technical data

Coil properties	<ul style="list-style-type: none"> * Inductance @ 1 kHz: 200mH \pm 15% * Resistance @ 25°C: 1'150 Ohm \pm 15% * Magnet polarity: north pole towards front face * Pole piece: diameter 2.7 mm
Signal output	<p>Using a sensor together with a toothed wheel having an involute gear form will generate a sinusoidal signal. Analysing the frequency will determine the rotational speed. The signal amplitude is proportional to the rate of change of magnetic flux generated by the pole wheel. In principle, it depends on the following parameters:</p> <ul style="list-style-type: none"> * Circumferential velocity of the toothed wheel * Module of the toothed wheel * Air gap between toothed wheel and sensor's front surface * Load impedance applied to the sensor (recommended is 10 kOhm) <p>Minimal voltage for 5 m/s circumferential speed, module 2 gear, 0.4 mm air gap and 10 kOhm load resistance: 9.2 Vpp</p>
Frequency range	Up to 30 kHz, lower limit depending on application

DSE 1810.01 AHZ

Variable Reluctance Speed Sensor

Housing	Stainless steel 1.4305, front side sealed hermetically and resistant against splashing water, oil, conducting carbon- or ferrous dust and salt mist. Electronic components potted in chemical and age proof synthetic resin. Dimensions according to drawing				
connector	<table border="1"><thead><tr><th>Jaquet connector type</th><th>Manufacturer code</th></tr></thead><tbody><tr><td>820E-36087</td><td>3-pol. CA02COM-E10S-3P-B</td></tr></tbody></table>	Jaquet connector type	Manufacturer code	820E-36087	3-pol. CA02COM-E10S-3P-B
Jaquet connector type	Manufacturer code				
820E-36087	3-pol. CA02COM-E10S-3P-B				
Requirements for Pole wheel	Toothed wheel of a ferrous material (e.g. Steel 1.0036). Optimal performance with <ul style="list-style-type: none">◆ Involute gear◆ Tooth width > 10mm◆ Side offset < 0.2 mm◆ Eccentricity < 0.2 mm				
Air gap between sensor and pole wheel	Depending on lowest circumferential speed which has to be detected and on trigger level.				
insulation	Housing and electronics galvanically separated (500 V/50 Hz/ 1 min)				
Protection class	IP68 (head)				

Further Information

Safety	All mechanical installations must be carried out by an expert. General safety requirements have to be met.
Connection	The sensors must be connected according to sensor drawing. Sensor wires are susceptible to radiated noise. Therefore, the following points have to be considered when connecting a sensor: The sensor wires must be laid as far as possible from large electrical machines. They must not run parallel in the vicinity of power cables. It is advantageous to keep the distance between sensor and instrument as short as possible. If the signal requirements are met, the sensor cable may be lengthened via a terminal box located in an IP20 connection area in accordance with EN 60529.
Installation	The sensor has to be aligned to the pole wheel according to the sensor drawing. Deviations in positioning may affect the performance and decrease the noise immunity of the sensor. During installation, the smallest possible pole wheel to sensor gap should be set. The amplitude of sensor's output signal depends on decreases with increasing air gap. Hence, the gap should however be set to prevent the face of the sensor ever touching the pole wheel. A sensor should be mounted with the middle of the face side over the middle of the pole wheel. Dependent upon the wheel width, a certain degree of axial movement is permissible. However, the middle of the sensor must be at minimum in a distance of 3 mm from the edge of the pole wheel under all operating conditions. A solid and vibration free mounting of the sensor is important. Eventual sensor vibration relative to the pole wheel can induce additional output pulses. The sensors are insensitive to oil, grease etc. and can be installed in arduous conditions.
Maintenance	Product cannot be repaired.
Transport	Product must be handled with care to prevent damage of the front face.
Storage	Product must be stored in dry conditions. The storage temperature corresponds to the operation temperature.
Disposal	Product must be disposed of properly, it must not be disposed as domestic waste.

DSE 1810.01 AHZ

Variable Reluctance Speed Sensor

CONTACT US

Tel +41 61 306 8822

jaquet.info@te.com

te.com/sensorsolutions

JAUQUET, TE Connectivity, and TE connectivity (logo) are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2017 TE Connectivity Ltd. family of companies All Rights Reserved.