



# VCS-01 VCS Series • Top or Bottom • Level Sensor

## Features

- ◆ Overall length less than 60mm
- ◆ Internal Fit
- ◆ 30mm diameter float
- ◆ Polypropylene Material


## Comments

- ◆ High or Low level sensing
- ◆ N/O or N/C by float reversal
- \* Reed Switch Reliability (UL File E153493)
- ◆ Exposed Magnet
- ◆ Interface Option Available

# **Applications**

- ◆ Water high or low Level
- ◆ Condensate level alarm
- ◆ Chemical high or low level
- ◆ Cooling systems
- ◆ Coolant level indication

| Material   |                                       | Cable                           |  |
|--|---------------------------------------|---------------------------------|--|
| Housing Material<br>Float Material   | Polypropylene<br>Foamed Polypropylene | Cable Length<br>Connection Type | 2 x 0.1M<br>Stripped Cables<br>22 AWG 16/0.2mm PVC<br>insulated<br>Black/Black |
| Contact Material   | Ruthenium                             | Cable Type                      |  |
| Float SG<br>Medium<br>Housing Colour<br>Float Colour   | 0.64<br>Water<br>Black<br>White       | Cable Colour                    |  |
| Mechanical Specifications  |                                       | Mounting                        |  |
| Shock  | 3 half-sine pulses of 11mS, 30G       | Thread                          | 1/8  |
| Vibration<br>Float Diameter<br>IP  | 35g up to 500Hz<br>30mm<br>IP65       | Fitment<br>Mounting             | Internal Fit<br>Top or Bottom entry  |
| Switching  |                                       | Technical Drawing               |  |
| Switch Action (Reed Switch) Max Switching Voltage VDC Max Switching Voltage VAC Max Switching Current Amps Max Switching Load Watt | SPST<br>200<br>250<br>1<br>30         | <u>VCS - 01</u>                 |  |
| Operate Mode   | N/C with float at bottom stop         |                                 |  |
| Contact Form   | A A                                   | 12 (0 47) 4                     | 1/8 " N.P.T  |



#### **NORTH AMERICA**

Measurement Specialties, Inc., a TE Connectivity Company Phone +1-800-522-6752 Email: <a href="mailto:customercare.hmpt@te.com">customercare.hmpt@te.com</a>

#### **EUROPE**

MEAS Deutschland GmbH(Europe) a TE Connectivity Company Phone: +49-800-440-5100 Email: customercare.tlse@te.com

#### **ASIA**

Measurement Specialties (China), Ltd., a TE Connectivity Company Phone: +86-0400-820-6015 Email: customercare.shzn@te.com

### TE.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Accustar, American Sensor Technologies, AST, ATEXIS, DEUTSCH, IdentiCal, TruBlue, KPSI, Krystal Bond, Microfused, UltraStable, Measurement Specialties, MEAS, Schaevitz, TE Connectivity, TE, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, product and company names mentioned herein may be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.