

### te.com



# **SERIES VI THERMISTORS**

± 0.05℃ accuracy Thermally Conductive Epoxy Coating Ø 2.4 mm Maximum Diameter 32 AWG Alloy 180 Leads RoHS Compliant

### **Features**

- Interchangeability
- Proven stability and reliability
- Rapid time response
- Alloy lead wires for reduced thermal conductivity ("stem effect")
- Thermally conductive epoxy coating
- Temperature range -40°C to +100℃
- Medical grade classification
- Custom probe assemblies available

#### **Applications**

- Temperature sensing, control and compensation
- Tight tolerance instrumentation
- Esophageal catheters
- Skin sensors
- Oral and rectal probes
- Pharmaceutical manufacturing equipment
- Temperature sensing, control and compensation

BetaCURVE series VI thermistors are small epoxy coated devices with solid tin plated lead wires. The series VI are specified with a temperature tolerance of +/-0.05°C over the range from +32°C to +44°C and are available in different nominal resistance values.

# **SERIES VI THERMISTORS**

# **Mechanical Details**



## DIMENSIONS

А	В		
76 ±3 mm	2.4 mm max.		

Note 1: 32 AWG Solid Alloy 180 Leads Note 2: Stycast 2850ft Epoxy

## **Reliability Data**

Test	Standard	Test Conditions	∆ <b>R25/R25</b>	Remarks	
Storage in dry heat	IEC 60068- 2-2	High temperature storage @+100℃. Duration: 1000 h	<0.5%	No mechanical damage	
Storage in dry heat	IEC 60068- 2-2	High temperature storage @+125℃ Duration: 1000 h	<1%	No mechanical damage	
Storage in damp heat, steady state	IEC60068-2- 78	Ambient Conditions: Temperature: +40℃ Relative humidity 93% Duration: 56 days	<1%	No mechanical damage	
Rapid temperature cycling	IEC60068-2- 14	Lower test temperature: -40℃ Upper test temperature: +125℃ Number of cycles: 1000	<1%	No mechanical damage	
Endurance		Pmax: 60mW Duration: 1000 h	<2%	No mechanical damage	

## **Product Details**

Part Number	Color Coding	Resistance @ +25°C	Resistance Tolerance	Tolerance Span	Beta Value 25/85	Dissipation Constant in Still Air @+25ºC	Time Response (Stirred Oil)
GA2.2K3A1AM	Brown	2,252Ω	± 0.05℃	32℃–44℃	3976	0.75 mW/ºC	<1 second
GA10K3A1AM	Yellow	10,000Ω	± 0.05℃	32℃–44℃	3976	0.75 mW/ºC	<1 second
GA10K4A1AM	Black	10,000Ω	± 0.05℃	32℃–44℃	3694	0.75 mW/ºC	<1 second

NORTH AMERICA Tel +1 800 522 6752 customercare.ando@te.com EUROPE Tel +31 73 624 6999 customercare.glwy@te.com ASIA Tel +86 0400 820 6015 customercare.chdu@te.com

## te.com/sensorsolutions

TE Connectivity, TE, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2019 TE Connectivity Corporation. All Rights Reserved.

Version # 08/2020

