

TECHNICAL DATA SHEET

LKZ...B4, PE, PEN

DESCRIPTION

Self adhesive printed vinyl labels overlaminated with a tough polyester film.
The adhesive is a permanent acrylic adhesive.

APPLICATION/USE

The LKZ self adhesive labels to identify copper-rails, connections or operating resources are supplied in different sizes on cards for rapid application.

PHYSICAL PROPERTIES	VALUE	TEST METHOD
Thickness	0.12mm Typical	
Adhesion <ul style="list-style-type: none">Stainless steel	500N/m (min)	FTM 1 (23°C, 300mm/min) 72 hr dwell

ENVIRONMENTAL AND STORAGE PROPERTIES	VALUE
Shelf Life	2 years storage at 23°C and 50% RH; without direct sunlight
Service Temperature	-30° to + 80°C
Minimum Application Temperature	+10°C

Product is compliant to EU RoHS Directive 2002/95/EC. This compliance information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information provided by our suppliers. This information is subject to change. For the latest compliance status, visit the Tyco Electronics RoHS Customer Support Center - <http://www.tycoelectronics.com/customersupport/rohssupportcenter>

All the above information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Tyco Electronics Corporation makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Tyco Electronics' only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Tyco Electronics Specifications are subject to change without notice. In addition Tyco Electronics reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.