




1. RING TO WIRE WELD TO WITHSTAND TENSILE FORCE OF 25 LBS.
2. WELD SURFACES TO BE FREE OF SPIKES AND CRACKS WHEN VIEWED AT 10X.
3. ASSEMBLY TO BE FREE OF GREASE, OIL AND FOREIGN MATERIAL WHEN VIEWED THROUGH NAKED EYE.
4. VISUAL INSPECT AT 10X FOR BURRS AND SHARP EDGES.

UNLESS OTHERWISE SPECIFIED - DIMENSIONS ARE IN INCHES - REMOVE ALL BURRS AND SHARP EDGES			<div></div>				
ASME Y14.5M-2018 APPLIES			TITLE:				
Drawn By NAVEENA HV	DATE 13-FEB-23	Scale NTS	Welded Assembly 17 Fr Pull Ring				
UNSPECIFIED TOLERANCE 3RD ANGLE 		$.x = \pm 0.1$ $.xx = \pm 0.01$ $.xxx = \pm 0.005$ $.xxxx = \pm 0.0005$  $\pm 0.5^*$					
MATERIAL: N/A		Specification No. 4117467				REV. 3	A4
FINISH: N/A		ERP No. 1000-3780-01				REV. 1	
HEAT TREAT: N/A		Customer Name: N/A					
Customer No. N/A			REV. N/A	SHEET 1 OF 1			
DO NOT SCALE DRAWING			THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF TE CONNECTIVITY CORPORATION UNAUTHORIZED USE OF THIS INFORMATION IS PROHIBITED				