

1. INTRODUCTION

The following guidelines are offered for the installation of Versaflex.

2. SAFETY

It is recommended that local safety regulations are adhered to and that installations are carried out in a well-ventilated area with adequate fume extraction. It is further recommended that operators wear appropriate Personal Protective Equipment (PPE) when installing and handling the products.

3. GENERAL INFORMATION

Versaflex, an expandable braided polyester sleeving is suited for the mechanical protection of wire harnesses, hoses, and all other applications where exceptional flexibility combined with superior abrasion/cut resistance is required. It also serves as an economical means for wire bundling that will not trap heat or moisture, expanding easily to fit over irregular shapes, then contracting to conform and grip.

4. INSTALLATION GUIDELINE

- a. Versaflex product is cold applied.
- b. Cut the tubing of required length. To prevent fraying, tubing should be cut to length using a hot knife.
- c. Make sure the cables / wires are clean before application of the tubing.
- d. Keep the cables / wires together and tight to have the proper bundling.
- e. Slide the product through cables to the required location.

Note: A small amount of heat can be applied at the ends of tubing for it to shrink and hold to the position.



5. REVISION HISTORY / REASON FOR CHANGE / RELATED DOCUMENTS

Rev	Date	Prepared By	Approved By	Remarks
A	November 2023	Kamalaravanan	Richard Kewell	New document