

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

**Closed End Splice Pressure Type Wire Connectors  
Type VS Wire Combinations**  
Catalog No. 34306, 34349, and 34864  
Circular Mil Range 3,248 to 4,872  
Use "18-16 VS or 16-14 ECV" Tooling  
Strip Length — 8.73 mm [.344 in.] Min  
10.32 mm [.406 in.] Max



90°C [194°F]  
Max

UL Listed and CSA Certified Wire Combinations  
Solid or Stranded Wire Sizes 22-16 AWG  
300 Volts Max

WIRE SIZE (AWG)	NO. OF WIRES	NO. OF ADDITIONAL WIRES OF ONE WIRE SIZE			
		22	20	18	16
22	1	4●	3	2	1
	2	3●	2	2	1
	3	2●	—	1	—
	4	1●	1	1	—
20	1	4	3	2	1
	2	2	—	1	1
	3	1	1	—	—
18	1	3	2	1-2	1
	2	1	1	1	—
16	1	1-2	1-2	1	—

● Use solid wire only.

**INSTRUCTIONS:** Use as shown for OEM applications.  
For all field applications, twist wires together before crimping.

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

**Closed End Splice Pressure Type Wire Connectors  
Type VS Wire Combinations**  
Catalog No. 34306, 34349, and 34864  
Circular Mil Range 3,248 to 4,872  
Use "18-16 VS or 16-14 ECV" Tooling  
Strip Length — 8.73 mm [.344 in.] Min  
10.32 mm [.406 in.] Max



90°C [194°F]  
Max

UL Listed and CSA Certified Wire Combinations  
Solid or Stranded Wire Sizes 22-16 AWG  
300 Volts Max

WIRE SIZE (AWG)	NO. OF WIRES	NO. OF ADDITIONAL WIRES OF ONE WIRE SIZE			
		22	20	18	16
22	1	4●	3	2	1
	2	3●	2	2	1
	3	2●	—	1	—
	4	1●	1	1	—
20	1	4	3	2	1
	2	2	—	1	1
	3	1	1	—	—
18	1	3	2	1-2	1
	2	1	1	1	—
16	1	1-2	1-2	1	—

● Use solid wire only.

**INSTRUCTIONS:** Use as shown for OEM applications.  
For all field applications, twist wires together before crimping.

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

**Closed End Splice Pressure Type Wire Connectors  
Type VS Wire Combinations**  
Catalog No. 34306, 34349, and 34864  
Circular Mil Range 3,248 to 4,872  
Use "18-16 VS or 16-14 ECV" Tooling  
Strip Length — 8.73 mm [.344 in.] Min  
10.32 mm [.406 in.] Max



90°C [194°F]  
Max

UL Listed and CSA Certified Wire Combinations  
Solid or Stranded Wire Sizes 22-16 AWG  
300 Volts Max

WIRE SIZE (AWG)	NO. OF WIRES	NO. OF ADDITIONAL WIRES OF ONE WIRE SIZE			
		22	20	18	16
22	1	4●	3	2	1
	2	3●	2	2	1
	3	2●	—	1	—
	4	1●	1	1	—
20	1	4	3	2	1
	2	2	—	1	1
	3	1	1	—	—
18	1	3	2	1-2	1
	2	1	1	1	—
16	1	1-2	1-2	1	—

● Use solid wire only.

**INSTRUCTIONS:** Use as shown for OEM applications.  
For all field applications, twist wires together before crimping.

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

**Closed End Splice Pressure Type Wire Connectors  
Type VS Wire Combinations**  
Catalog No. 34306, 34349, and 34864  
Circular Mil Range 3,248 to 4,872  
Use "18-16 VS or 16-14 ECV" Tooling  
Strip Length — 8.73 mm [.344 in.] Min  
10.32 mm [.406 in.] Max



90°C [194°F]  
Max

UL Listed and CSA Certified Wire Combinations  
Solid or Stranded Wire Sizes 22-16 AWG  
300 Volts Max

WIRE SIZE (AWG)	NO. OF WIRES	NO. OF ADDITIONAL WIRES OF ONE WIRE SIZE			
		22	20	18	16
22	1	4●	3	2	1
	2	3●	2	2	1
	3	2●	—	1	—
	4	1●	1	1	—
20	1	4	3	2	1
	2	2	—	1	1
	3	1	1	—	—
18	1	3	2	1-2	1
	2	1	1	1	—
16	1	1-2	1-2	1	—

● Use solid wire only.

**INSTRUCTIONS:** Use as shown for OEM applications.  
For all field applications, twist wires together before crimping.