

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

**Closed End Splice Pressure Type Wire Connectors
Type ECV Wire Combinations
Catalog No. 50920**

**Circular Mil Range 3,248 to 4,872 — Use “18-16 ECVG” Tooling
Strip Length — 10.32 mm [.406 in.] Min
11.91 mm [.469 in.] Max**



105°C [222°F]
Max

**UL Listed and CSA Certified Wire Combinations
Solid or Stranded Wire Sizes 22-16 AWG
600 Volts Max Building Wiring 1000 Volts Max Fixture or Sign**



90°C [194°F]
Max

WIRE SIZE (AWG)	NO. OF WIRES	NO. OF ADDITIONAL WIRES OF ONE WIRE SIZE			
		22	20	18	16
22	1	4	3	2	1
	2	3	2	2	1
	3	2	2	1	—
	4	1	1	1	—
20	1	4	3	2	1
	2	2	2	1	1
	3	1	1	—	—
18	1	3	2	1-2	1
	2	1	1	1	—
16	1	1-2	1-2	1	—

INSTRUCTIONS: Twist wires together before crimping.

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

**Closed End Splice Pressure Type Wire Connectors
Type ECV Wire Combinations
Catalog No. 50920**

**Circular Mil Range 3,248 to 4,872 — Use “18-16 ECVG” Tooling
Strip Length — 10.32 mm [.406 in.] Min
11.91 mm [.469 in.] Max**



105°C [222°F]
Max

**UL Listed and CSA Certified Wire Combinations
Solid or Stranded Wire Sizes 22-16 AWG
600 Volts Max Building Wiring 1000 Volts Max Fixture or Sign**



90°C [194°F]
Max

WIRE SIZE (AWG)	NO. OF WIRES	NO. OF ADDITIONAL WIRES OF ONE WIRE SIZE			
		22	20	18	16
22	1	4	3	2	1
	2	3	2	2	1
	3	2	2	1	—
	4	1	1	1	—
20	1	4	3	2	1
	2	2	2	1	1
	3	1	1	—	—
18	1	3	2	1-2	1
	2	1	1	1	—
16	1	1-2	1-2	1	—

INSTRUCTIONS: Twist wires together before crimping.

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

**Closed End Splice Pressure Type Wire Connectors
Type ECV Wire Combinations
Catalog No. 50920**

**Circular Mil Range 3,248 to 4,872 — Use “18-16 ECVG” Tooling
Strip Length — 10.32 mm [.406 in.] Min
11.91 mm [.469 in.] Max**



105°C [222°F]
Max

**UL Listed and CSA Certified Wire Combinations
Solid or Stranded Wire Sizes 22-16 AWG
600 Volts Max Building Wiring 1000 Volts Max Fixture or Sign**



90°C [194°F]
Max

WIRE SIZE (AWG)	NO. OF WIRES	NO. OF ADDITIONAL WIRES OF ONE WIRE SIZE			
		22	20	18	16
22	1	4	3	2	1
	2	3	2	2	1
	3	2	2	1	—
	4	1	1	1	—
20	1	4	3	2	1
	2	2	2	1	1
	3	1	1	—	—
18	1	3	2	1-2	1
	2	1	1	1	—
16	1	1-2	1-2	1	—

INSTRUCTIONS: Twist wires together before crimping.

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

**Closed End Splice Pressure Type Wire Connectors
Type ECV Wire Combinations
Catalog No. 50920**

**Circular Mil Range 3,248 to 4,872 — Use “18-16 ECVG” Tooling
Strip Length — 10.32 mm [.406 in.] Min
11.91 mm [.469 in.] Max**



105°C [222°F]
Max

**UL Listed and CSA Certified Wire Combinations
Solid or Stranded Wire Sizes 22-16 AWG
600 Volts Max Building Wiring 1000 Volts Max Fixture or Sign**



90°C [194°F]
Max

WIRE SIZE (AWG)	NO. OF WIRES	NO. OF ADDITIONAL WIRES OF ONE WIRE SIZE			
		22	20	18	16
22	1	4	3	2	1
	2	3	2	2	1
	3	2	2	1	—
	4	1	1	1	—
20	1	4	3	2	1
	2	2	2	1	1
	3	1	1	—	—
18	1	3	2	1-2	1
	2	1	1	1	—
16	1	1-2	1-2	1	—

INSTRUCTIONS: Twist wires together before crimping.