



POE-xxs-afi

Power-Over-Ethernet

POWER-OVER-ETHERNET

Power Supply/Inserter

The active Power-Over-Ethernet (POE) splitter from Laird Technologies gives carrier class performance in a low cost system. With its IEEE 802.3af compatibility and advanced auto-sensing algorithm, it accepts POE power from any IEEE 802.3af router or power supply. The overload and short circuit protection shuts down power immediately when a short circuit is detected without any damage to the POE system. Power (36 to 60 V) is expected on ethernet pins 4/5 (V+) and 7/8 (V-) as per the IEEE 802.3af standard or pins 1,2,3,6 (Cisco Standard).

Using POE to power remote devices has several advantages including;

- The power supply can be centrally located where it can be attached to an uninterruptible power supply.
- Power can be supplied over long distances, up to 300 feet.
- Power can be available wherever network access is available.
- The user has the ability to easily power-on reset the attached equipment from a remote location.

The active POE splitter from Laird can be used by the original equipment manufacturer to supply power to remote equipment and devices without the expense of building in separate POE functionality into their equipment. These devices are a good fit for the industrial market for sensing and remote video applications.

FEATURES AND BENEFITS

- IEEE 802.3af POE active splitter
- Choice of 5, 9, 12 or 24 VDC regulated power
- 100 mohm/1000 VDC isolation
- Advanced auto-sensing intelligent algorithm
- Overload and short circuit protection
- Advanced switching technology - runs cool
- Complies with IEEE 802.3af POE standard
- FCC and CE approved
- Compatible with IEEE 802.3af routers including Cisco and Netgear

APPLICATIONS

- Remote routers, access points and bridges
- Remote networking equipment
- SOHO equipment
- IP camera systems
- VOIP systems
- IP phone systems
- WiMAX

ACTIVE SPLITTER WITH ISOLATION

Input Voltage	36 to 60 VDC
Output Voltage	POE-5s 5 VDC@ 2.4 A POE-9s 9 VDC @ 1 A POE-12s 12 VDC @ 1 A POE-24s 24 VDC @ .5 A
Output Ripple	1% Max
Switching Frequency	100 KHz Typ
Line Regulation	+/- 0.5%
Load Regulation	+/- 1%
Isolation Voltage	1000 VDC
Isolation Resistance	100 mohms (min)
Input Set Class Resistance	25 kohms
Operating Temperature	-10 to +60°C
Storage Temperature	-20 to +85°C
Operating Humidity	5% to 90% non condensing
Size (L x W x H)	83 x 76 x 38 mm (3.25 x 3 x 1.5 inches)
Weight	130 gm (4.6 oz)
Data/POE IN Conn.	RJ45 Socket
Data OUT Conn.	12 in Cable with RJ45 Plug
VDC OUT Conn.	12 in Cable with 5.5 x 2.1 x 12 mm Adapter Plug

COMPLIANCE

IEEE	802.3af POE Standard
EMI	EN55022 (CISPR22) class B Meets CE
EMS	EN61000-4-2,3,4,5,6,8,11

SYSTEM ORDERING

POE-5s-afi 5 VDC 2.4 A Active 802.3af POE Splitter with isolation
POE-9s-afi 9 VDC 1 A Active 802.3af POE Splitter with isolation
POE-12s-afi 12 VDC .67 A Active 802.3af POE Splitter with isolation
POE-24s-afi 24 VDC .5 A Active 802.3af POE Splitter with isolation

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE Connectivity, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

©2021 TE Connectivity. All Rights Reserved.

11/21 Original

