

DESIGN CONTROL REQUIRED			<table><tr><th colspan="4">REVISIONS</th></tr><tr><th>REV</th><th>DESCRIPTION</th><th>DATE</th><th>APPROVED</th></tr><tr><td>01₀</td><td>RELEASED</td><td>3/7/95</td><td>M.M.</td></tr></table>				REVISIONS				REV	DESCRIPTION	DATE	APPROVED	01 ₀	RELEASED	3/7/95	M.M.																																																																													
			REVISIONS																																																																																												
			REV	DESCRIPTION	DATE	APPROVED																																																																																									
01 ₀	RELEASED	3/7/95	M.M.																																																																																												
<table><tr><td>HOUSING MOUNTING NUT</td><td>BRASS PER QQ-B-626 COMP. 360, HALF HARD</td><td>NICKEL PLATE PER QQ-N-290</td></tr><tr><td>HOUSING</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303</td><td>PASSIVATE PER ASTM-A380</td></tr><tr><td>DIELECTRIC</td><td>TFE FLUOROCARBON PER ASTM-D-1457</td><td>N/A</td></tr><tr><td>CENTER CONTACT</td><td>BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>LOCKWASHER</td><td>PHOSPHOR BRONZE PER QQ-B-750, GRADE B2</td><td>NICKEL PLATE PER QQ-N-290</td></tr><tr><td>GASKET</td><td>SILICONE RUBBER PER ZZ-R-765</td><td>N/A</td></tr></table>				HOUSING MOUNTING NUT	BRASS PER QQ-B-626 COMP. 360, HALF HARD	NICKEL PLATE PER QQ-N-290	HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380	DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A	CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204	LOCKWASHER	PHOSPHOR BRONZE PER QQ-B-750, GRADE B2	NICKEL PLATE PER QQ-N-290	GASKET	SILICONE RUBBER PER ZZ-R-765	N/A																																																																										
HOUSING MOUNTING NUT	BRASS PER QQ-B-626 COMP. 360, HALF HARD	NICKEL PLATE PER QQ-N-290																																																																																													
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380																																																																																													
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A																																																																																													
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204																																																																																													
LOCKWASHER	PHOSPHOR BRONZE PER QQ-B-750, GRADE B2	NICKEL PLATE PER QQ-N-290																																																																																													
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A																																																																																													
<table><tr><th>ELECTRICAL</th><th>MECHANICAL</th><th>ENVIRONMENTAL</th></tr><tr><td>Nominal Impedance (Ohms) 50</td><td>Interface Dimensions</td><td>Temperature Rating -65°C to +125°C</td></tr><tr><td>Frequency Range (GHz) DC to 4</td><td>BNC MIL-STD-348A Fig. 301.2</td><td>Vibration MIL-STD-202, Method 204, Condition D</td></tr><tr><td>Volt Rating (VRMS MAX) @ Sea Level 335</td><td>OSM MIL-STD-348A Fig. 310.2</td><td>Shock MIL-STD-202, Method 213, Condition I</td></tr><tr><td>VSWR 1.30 Max at 0.5 to 4.0 GHz</td><td>Recommended Mating Torque 4-6 In-Lbs</td><td>Thermal Shock MIL-STD-202, Method 107, Condition C, Except High Temp</td></tr><tr><td>Insertion Loss (dB MAX) 0.2√f(GHz)</td><td>Mating Characteristics:</td><td>Moisture Resistance MIL-STD-202, Method 106 Shall Be Omitted</td></tr><tr><td>RF Leakage (dB MIN) -55, 2 to 3 GHz</td><td></td><td>Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray</td></tr><tr><td>Corona, 70,000 Ft (VRMS MIN) 250</td><td>Insertion (Lbs Max) 2.0 3.0</td><td></td></tr><tr><td>Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1500</td><td>Withdrawal (Oz Min) 2.0 1.0</td><td></td></tr><tr><td>Contact Resistance (Milliohms MAX)</td><td>Force to Engage/Disengage</td><td></td></tr><tr><td>Center Contact 4.1</td><td>Longitudinal</td><td></td></tr><tr><td>Outer Contact 2.2</td><td>Force (Lb Max) 3.0 N/A</td><td></td></tr><tr><td>RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670</td><td>Torque (In-Lb Max) 2.5 2.0</td><td></td></tr><tr><td>I.R.(Megohms MIN) 5000</td><td>Contact Retention</td><td></td></tr><tr><td></td><td>Axial (Lbs) 6.0</td><td></td></tr><tr><td></td><td>Radial (In-Oz) 4.0</td><td></td></tr><tr><td></td><td>Weight (Grams)</td><td></td></tr></table>			ELECTRICAL	MECHANICAL	ENVIRONMENTAL	Nominal Impedance (Ohms) 50	Interface Dimensions	Temperature Rating -65°C to +125°C	Frequency Range (GHz) DC to 4	BNC MIL-STD-348A Fig. 301.2	Vibration MIL-STD-202, Method 204, Condition D	Volt Rating (VRMS MAX) @ Sea Level 335	OSM MIL-STD-348A Fig. 310.2	Shock MIL-STD-202, Method 213, Condition I	VSWR 1.30 Max at 0.5 to 4.0 GHz	Recommended Mating Torque 4-6 In-Lbs	Thermal Shock MIL-STD-202, Method 107, Condition C, Except High Temp	Insertion Loss (dB MAX) 0.2√f(GHz)	Mating Characteristics:	Moisture Resistance MIL-STD-202, Method 106 Shall Be Omitted	RF Leakage (dB MIN) -55, 2 to 3 GHz		Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray	Corona, 70,000 Ft (VRMS MIN) 250	Insertion (Lbs Max) 2.0 3.0		Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1500	Withdrawal (Oz Min) 2.0 1.0		Contact Resistance (Milliohms MAX)	Force to Engage/Disengage		Center Contact 4.1	Longitudinal		Outer Contact 2.2	Force (Lb Max) 3.0 N/A		RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670	Torque (In-Lb Max) 2.5 2.0		I.R.(Megohms MIN) 5000	Contact Retention			Axial (Lbs) 6.0			Radial (In-Oz) 4.0			Weight (Grams)		<table><tr><td colspan="2">UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON</td><td colspan="2">DRAWN BY M.M. DATE 3/7/95</td><td colspan="2" rowspan="3"> AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599</td></tr><tr><td colspan="2">FRAC. DEC. ANGLES</td><td colspan="2">CHECKED BY</td></tr><tr><td colspan="2">± 1/64 ±.005 ± 1°</td><td colspan="2">APPD BY</td></tr><tr><td colspan="2">These drawings and specifications are the property of M/A-COM Interconnect Division and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of items without written permission.</td><td colspan="2">USE ASS'Y PROCEDURE</td><td colspan="2">TITLE BNC JACK TO OSM JACK BULKHEAD FEEDTHROUGH ADAPTER</td></tr><tr><td colspan="2">NO. AP. N/A</td><td colspan="2">SIZE B</td><td>CODE IDENT NO. 26805</td><td>REV 01₀</td></tr><tr><td colspan="2"></td><td colspan="2">SCALE 2:1</td><td colspan="2">1250-0562-00</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2">SHEET 1 OF 1</td></tr></table>				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON		DRAWN BY M.M. DATE 3/7/95		AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599		FRAC. DEC. ANGLES		CHECKED BY		± 1/64 ±.005 ± 1°		APPD BY		These drawings and specifications are the property of M/A-COM Interconnect Division and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of items without written permission.		USE ASS'Y PROCEDURE		TITLE BNC JACK TO OSM JACK BULKHEAD FEEDTHROUGH ADAPTER		NO. AP. N/A		SIZE B		CODE IDENT NO. 26805	REV 01 ₀			SCALE 2:1		1250-0562-00						SHEET 1 OF 1	
ELECTRICAL	MECHANICAL	ENVIRONMENTAL																																																																																													
Nominal Impedance (Ohms) 50	Interface Dimensions	Temperature Rating -65°C to +125°C																																																																																													
Frequency Range (GHz) DC to 4	BNC MIL-STD-348A Fig. 301.2	Vibration MIL-STD-202, Method 204, Condition D																																																																																													
Volt Rating (VRMS MAX) @ Sea Level 335	OSM MIL-STD-348A Fig. 310.2	Shock MIL-STD-202, Method 213, Condition I																																																																																													
VSWR 1.30 Max at 0.5 to 4.0 GHz	Recommended Mating Torque 4-6 In-Lbs	Thermal Shock MIL-STD-202, Method 107, Condition C, Except High Temp																																																																																													
Insertion Loss (dB MAX) 0.2√f(GHz)	Mating Characteristics:	Moisture Resistance MIL-STD-202, Method 106 Shall Be Omitted																																																																																													
RF Leakage (dB MIN) -55, 2 to 3 GHz		Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray																																																																																													
Corona, 70,000 Ft (VRMS MIN) 250	Insertion (Lbs Max) 2.0 3.0																																																																																														
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1500	Withdrawal (Oz Min) 2.0 1.0																																																																																														
Contact Resistance (Milliohms MAX)	Force to Engage/Disengage																																																																																														
Center Contact 4.1	Longitudinal																																																																																														
Outer Contact 2.2	Force (Lb Max) 3.0 N/A																																																																																														
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670	Torque (In-Lb Max) 2.5 2.0																																																																																														
I.R.(Megohms MIN) 5000	Contact Retention																																																																																														
	Axial (Lbs) 6.0																																																																																														
	Radial (In-Oz) 4.0																																																																																														
	Weight (Grams)																																																																																														
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON		DRAWN BY M.M. DATE 3/7/95		AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599																																																																																											
FRAC. DEC. ANGLES		CHECKED BY																																																																																													
± 1/64 ±.005 ± 1°		APPD BY																																																																																													
These drawings and specifications are the property of M/A-COM Interconnect Division and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of items without written permission.		USE ASS'Y PROCEDURE		TITLE BNC JACK TO OSM JACK BULKHEAD FEEDTHROUGH ADAPTER																																																																																											
NO. AP. N/A		SIZE B		CODE IDENT NO. 26805	REV 01 ₀																																																																																										
		SCALE 2:1		1250-0562-00																																																																																											
				SHEET 1 OF 1																																																																																											