THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION - ,- .
© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST
CM	53

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A1	RELEASED PER ECR-17-015922	07NOV2017	BDA	KR

1 MATES WITH APPROPRIATE UNIVERSAL MATE-N-LOK ™ CAP OR HEADER.

2 SMALL NICKS ARE PERMITTED ON THE CIRCUIT TOWERS WHICH COULD INCREASE THE INITIAL HOUSING MATING FORCE BY UP TO 4.4 NEWTONS [1.0 LBS]. NO INDIVIDUAL NICKED TOWER SHALL INCREASE THIS FORCE BY OVER 2.2 NEWTONS [.5 LBS].

3 DIMENSIONS SHOWN REPRESENT PRODUCT IN DRY, AS MOLDED, CONDITION. ADDITIONAL 2% GROWTH DUE TO SUBSEQUENT MOISTURE ABSORPTION MAY OCCUR AND SHOULD BE ACCOUNTED FOR.

△4 FOUR RIBS EQUALLY SPACED, NO SPECIFIC ORIENTATION, OR SIX RIBS EQUALLY SPACED, NO SPECIFIC ORIENTATION, OPTIONAL

△5 MOLDING COMPOUND; 3-703939-8, (66/6 NYLON, RED, V0) NO OTHER RESIN MAY BE USED OR SUBSTITUTED.









OPTIONAL CONSTRUCTION △4





△5	2029457-1
MATERIAL	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± 0.51 [.020]
3 PLC ± -
4 PLC ± -
ANGLES ± 0° 30'

MATERIAL: SEE TABLE
FINISH: -

DWN JR RUTH 13DEC13
CHK TOM MICHIELUTTI 13DEC13
APVD TOM MICHIELUTTI 13DEC13
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT

TE Connectivity

NAME
PLUG,
SHORT LATCH,6 CIRCUIT,
UNIVERSAL MATE-N-LOK ™

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C-2029457	—

CUSTOMER DRAWING | SCALE 4:1 | SHEET 1 OF 1 | REV A1