

17

3309

signal max. 7 A* 125 V (AC/DC)

2000 V

Data according to VDE 0110/EN61984, Paragraph 6.19.2.2

zinc diecast / chromated

PBT, UL 94 / V0 FKM

2000 m

500

3 ĪII

-20 °C to 130 °C when connected IP 66/67

Technical Data

rated insulation voltage (L-L)

number of pins

protection type

rotation range **Electrical Data**

rated current rated voltage

mating cycles

Material

housing insulation insert

seals

pollution degree over voltage category

max. height for operation

Contacts (not part of product contents)

Tools (not part of product contents)

temperature range

623 Receptacle angled rotatable

speedtec

17-pin insulation insert Code 0° housing code 1 flange mount /Flange 25x25

A ED C 139 NN 00 00 1115 000 A G C 139 N 00 00 1115 000



Contact Arrangement mating view




© 2018 TE Connectivity

TE Connectivity, TE connectivity (logo), intercontec (logo) and speedtec are trademarks.


While TE Connectivity (TE) has made every reasonable effort to ensure the accuracy of the information in this presentation, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this article are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

TE Connectivity Industrial GmbH Bernrieder Straße 15 94559 Niederwinkling, Deutschland Tel.: +49 9962 2002-0 Fax: +49 9962 2002-70 E-Mail: intercontec@te.com Web: www.intercontec.biz





Montagefenster



Main Dimensions Receptacle angled rotatable

*for max. wire cross-section pay attention to the cross-section of used contacts

2018 08. 29. ssue: