

4

3

2

1

THIS DRAWING IS UNPUBLISHED

RELEASED FOR PUBLICATION

20

© COPYRIGHT 2015

BY - TE CONNECTIVITY

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

| P | LTR | DESCRIPTION | DATE | DWN | APVD |
|---|-----|-----------------------------|-----------|-----|------|
| | A | NEW DRAWING | 08JUL2016 | MGM | CE |
| | A1 | REVISED PER PCN E-19-012270 | 05AUG2019 | MK | PV |

SECTION A-A
Schnitt

NOTES

Bemerkungen

- BULK PACKAGING IN CORRUGATED BOX
Lose im Beutel und Versandkarton
- ALL SYMMETRY DIMENSION $\frac{\text{---}}{\text{---}}$ 0.1
Alle Symmetriemaße
- SUITABLE SOCKET CONTACT SEE DRAWING: DARS24263
Passender Buchsenkontakt siehe Zeichnung: DARS24263

SCALE 2:1
Maßstab

| | REF. | NOTE |
|-----------------------------------|-----------------------------------|-------------------------------|
| CRIMPING TOOL Crimpzange | OUT0405-0110ASO (Daniels M317) | Position - Stellung N°8 |
| LOCATOR Stellungsregler | (DANIELS TP1024) | |
| EXTRACTION TOOL Ausbauwerkzeug | OUTCC IEXT-E0100 | |

IMPORTANT: THE POSITION MAY
VARY ACCORDING TO THE REAL WIRE
CROSS SECTION AND COMPOSITION.Wichtig:
Die Position kann entsprechend dem
tatsächlichen Drahtdurchmesser
und -aufbau variieren.

| REV | QTY Stueck | REV | PLATING Oberfläche | TE ORDER-NO. TE Bestell-Nr. | DESCRIPTION Beschreibung | ITEM NO |
|-----|---------------|-----|-----------------------|--------------------------------|-----------------------------|------------|
| A | 1 | A | - | DARS24296-000A3 | CLIP Clip | 2 |
| | 1 | A | Ag | | PIN BODY Stiftkörper | 1 |

| | | | | | | | | | | | | | | | | | | |
|--|---|--|-----------------|---------------------|-------------------------------|---|--|---|-------|---|-------|---|--------|--|-------|------------------|--|------------|
| THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONING AND TOLERANCING PER GPS (ISO STANDARDS) | | DWN 06 JUL 2016 C.HANDRASHEKAR.S | | | | | | | | | | | | | | | | |
| DIMENSIONS: mm | | CHK 08 JUL 2016 C.FINZER | | | | | NAME PIN CONTACT 6 SQMM, CAR CONNECTOR Stiftkontakt 6 SQMM | | | | | | | | | | | |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: | | APVD 08 JUL 2016 C.FBERWEIN | PRODUCT SPEC | | RESTRICTED TO | | | | | | | | | | | | | |
| <table border="1"> <tr> <td>0 PLC</td> <td>±</td> <td rowspan="5">ACC. TO ISO 8015</td> </tr> <tr> <td>1 PLC</td> <td>±</td> </tr> <tr> <td>2 PLC</td> <td>±</td> </tr> <tr> <td>3 PLC</td> <td>±</td> </tr> <tr> <td>4 PLC</td> <td>±</td> </tr> <tr> <td colspan="2">ANGLES</td> <td>±0.5°</td> </tr> </table> | | 0 PLC | ± | ACC. TO ISO 8015 | 1 PLC | ± | 2 PLC | ± | 3 PLC | ± | 4 PLC | ± | ANGLES | | ±0.5° | APPLICATION SPEC | | SIZE A3 |
| 0 PLC | ± | ACC. TO ISO 8015 | | | | | | | | | | | | | | | | |
| 1 PLC | ± | | | | | | | | | | | | | | | | | |
| 2 PLC | ± | | | | | | | | | | | | | | | | | |
| 3 PLC | ± | | | | | | | | | | | | | | | | | |
| 4 PLC | ± | | | | | | | | | | | | | | | | | |
| ANGLES | | ±0.5° | | | | | | | | | | | | | | | | |
| MATERIAL SEE TABLE Siehe Tabelle | | FINISH SEE TABLE | WEIGHT 7.8 g | CAGE CODE - | DRAWING NO DARS24296-000A3 | | | | | | | | | | | | | |
| CUSTOMER DRAWING | | | SCALE 5:1 | SHEET 1 OF 1 | REV A1 | | | | | | | | | | | | | |

1470-19 (3/11)