


## Application Note

### RF Coaxial Connector Gender Naming

RF coaxial connectors come in a wide variety of sizes, attachment types (including cable-termination, panel-mount and surface-mount) and coupling systems (most commonly screw-on and snap-on). All have the common traits of a center conductor to conduct a radio frequency signal and a connector housing to make and hold the connection as well as provide grounded shielding of the signal as depicted in the SMA connectors in Figure 1.



**Figure 1. SMA Connectors**

The ways in which the two housings and center conductors engage to make both physical and electrical connection have been treated as physical genders, male and female, to describe which half of the connection is which. There are a number of other terms used for the same purpose and they generally align as shown in Figure 2.




**Figure 2. Typical RF Coaxial Connector Gender Terms**

Of these terms, female or socket, and male or pin, are most often used to refer to the center conductor of the connector while plug and jack are most often used to refer to the housing connection. When considering the mechanical connection which the housing creates between the two connectors, the plug is generally the connector having the housing that initiates and/or holds the mechanical connection. However, there are no rules or even firm conventions across RF industry.

The SMA connector shown in Figure 1 is likely the most common and well-known RF coaxial connector in use. Using that as the “standard,” the connector on the left has a housing that is a plug with a male, or pin, center conductor and the whole assembly is commonly called an SMA plug. The connector on the right is a jack with a female, or socket, center conductor and the assembly is commonly called an SMA Jack. If the connector on the right was intended for printed circuit board mounting, it might be referred to as a receptacle instead of jack.


However, there exists what is called a reverse-polarity SMA (RP-SMA) connector which reverses the center conductors. With an RP-SMA connector, the plug housing has a female/socket center conductor and the jack housing has a male/pin center conductor.



**Figure 3. RP-SMA Connectors**

Other connector families offer even greater challenges in understanding connector gender naming. U.FL-type connectors, also called MHF or UMCC connectors depending on manufacturer, often follow the RP-SMA format as the norm.

With U.FL connectors, as shown in Figure 4, the housing on the cable is a plug, but in almost all cases, particularly when used as the cabled connection for an antenna, the center conductor is female/socket. The opposite connector is seldom used on a cable and is most often mounted on a printed circuit board and called a receptacle even though it has a male/pin center conductor. While this may be confusing, there is a rationale for it. U.FL receptacles on a PCB board use the robust pin center conductor to last the life of the board which may require many connects and disconnects, while the more easily replaceable cabled plug must maintain the mechanical connection but is not expected to withstand as many interconnect cycles as the receptacle.



**Figure 4. U.FL Connectors**

Other connector families exhibit similar traits as well as inconsistencies. Therefore, careful review of RF coaxial connector genders is required in design and specification.

### RF Coaxial Connector Selection Best Practices

When selecting connectors there are a few best practices to leverage to ensure that the components selected meet the needs and requirements of the project.

1. Do not rely solely on the part number to convey connector gender. The number may reflect naming for the housing or center conductor, or nothing at all.
2. Focus on the center conductor and housing descriptions which are often provided on distributor websites and in manufacturer data.
3. Be wary of web page descriptions, instead leverage photographs and mechanical drawings which are more typically passed through more stringent review than marketing copy.
4. Consult a field applications engineer or sales to confirm connector characteristics before committing to the design.

---

## TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

## te.com

TE Connectivity, TE, TE connectivity (logo), Linx and Linx Technologies are trademarks owned or licensed by the TE Connectivity Ltd. family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE Connectivity product is installed. Useful lifetime of the original end product may vary but is not warrantied to exceed one (1) year from the original date of the end product purchase.

©2023 TE Connectivity. All Rights Reserved.

08/23 Original

---