



HEAT SHRINK MACHINES

FOR RAYCHEM HEAT SHRINK PRODUCTS FROM TE CONNECTIVITY



Machines:



	 RBK X1 & X1C	 XS-D1	 XB17 & XB-19	 Model 105
 In-Line Splice	✓	✓	✓	✓
 End (Stub) Splice	Fixture needed	✓	Fixture needed	Customized fixture needed
 Ring Terminal	Fixture needed	✓	Fixture needed	Customized fixture needed
 Wire Bundle	✗	✓	Limited to size	✓

RBK X1 PROCESSOR

Technical Data

- Electrical supply: 220 – 240V, 50/60 Hz
- Power consumption: 3A (max.)
- Maximum temperature setting: 500° C (possible to reach 600° C)
- Machine cycle time: 1 to 99 secs. (usual working time is 6 to 20 sec.)
- Total system noise: <80 dB
- Dimensions: 419 x 500 x 218 mm
- Weight: 24 kg

Product Range/Sizes

- Tubing diameter: Up to 19 mm (max)
- Tubing length: Up to 65 mm (max)



MACHINE ORDERING INFORMATION

Description	PN
RBK X1	2234800-1
RBK X1 CE	2234800-2
RBK X1 Air Cooled	1-2234800-3
RBK X1 CE Air Cooled	1-2234800-4

ACCESSORIES ORDERING INFORMATION

Description	PN
Handheld Barcode Scanner	2234781-1
110V-220V AC transformer with US AC cord	2234986-1
Handheld Barcode Scanner (wireless)	9-2375314-9
Communication Cable	2234787-1

MES (custom only)

CALIBRATION SOLUTIONS ORDERING INFORMATION

Description	PN
Calibration Kit (includes probe & cable)	1-2389761-2
Standard UHI Temperature Calibration Probe	288869-000
Connection Cable (applied with probe)	9-2375314-6

Product Features

The RBK X1 processor is a semi-automatic unit designed specifically for sealing wire bundles, splice terminals and ring terminals. The RBK X1 features long life heating elements, operator key lock/password protection levels and individual selections for Installation times, temperature and product size information.

THE RBK X1 CAN OPERATE IN SEVERAL MODES:

- Stand-alone – operator sets time and temperature
- Sequenced – preset times and temperatures can be sequenced automatically and can also be randomly selected from sequence stored
- Communication with upstream ultrasonic welder can allow time and temperature to be automatically set without operator intervention

HEAT SHRINK MACHINES

FOR RAYCHEM HEAT SHRINK PRODUCTS FROM TE CONNECTIVITY

RBK X1 Operation:

The operator is able to efficiently load both machines and minimize dead time. Installing splice sealing products immediately after welding gives reduced installation time and early possible mechanical protection for the welded joint.

The operator positions the splice sealing product centrally over the splice joint and then locates the assembly into the gripper mechanism. Pushing the two start buttons initiates the machine cycle, bringing the heating chamber into place over the joint area. The heating chamber remains in place for the set period and then returns to the rest position. The wire assembly is automatically ejected, with the splice sealing product installed and the joint area sealed, insulated and strain relieved.

FIXTURE SOLUTIONS

Description	PN
Stub Splice Fixture	981721-000 [†]
Air Cool Connection Box (applied with stub splice fixture 981721-000)	1-529533-7

[†] Custom tooling will be quoted separately

MULTI-PURPOSE FIXTURE SOLUTIONS

Description	PN
Cable Clamping Fixture (without AC)	2234786-1
Cable Clamping Fixture (with AC)	2234786-2

Both multi-purpose fixtures accept customized tooling

RBK X1C PROCESSOR

Technical Data

- Electrical supply: 220 – 240V, 50/60 Hz
- Power consumption: 3A (max.)
- Maximum temperature setting: 500° C (possible to reach 600° C)
- Machine cycle time: 1 to 99 secs. (usual working time is 6 to 20 sec.)
- Total system noise: <80 dB
- Dimensions: 555 x 500 x 232 mm
- Weight: 32 Kg

Product Range/Sizes

- Tubing diameter: Up to 19 mm (max)
- Tubing length: Up to 60 mm (max)



MACHINE ORDERING INFORMATION

Description	PN
Centering Device Unit Only (for upgrades)	2369600-1
RBK X1C	2376800-1
RBK X1C CE	2376800-2
RBK X1C Air Cooled	1-2376800-3
RBK X1C CE Air Cooled	1-2376800-4

RBX X1C FIXTURE

Description	PN
RBK X1C fixture	2369606-1

HEAT SHRINK MACHINES

FOR RAYCHEM HEAT SHRINK PRODUCTS FROM TE CONNECTIVITY

Product Features

Based on the RBK X1 platform, the RBK X1C machine includes an automatic centering device that help to maintain accurate wire and tubing placement.


Programmable splice sensors electronically verify that wires are accurately positioned to begin the centering process. Upon validation of wire placement, the system will activate automated guide arms to properly position the tubing product into place for the heat shrink cycle to begin.

A CLOSER LOOK AT HOW THE CENTERING DEVICE WORKS

Programmable sensors locate splice location for proper wire alignment



Automated guide arms position tubing into place for the heat cycle to begin



XB-17 BELT HEATER

Technical Data

- Electrical supply: [PN 2375310-2] 110 VAC, 1Ø; [PN 2375310-1] 220 VAC, 1Ø
- Heating elements: 2 ea. 1000 Watts stamped foil infrared with quartz face
- Maximum temperature setting: 600° C
- Air flow (cooling): 2 – 100 CFM fans in the upper heater housing
- Conveyor belt system: Double sided timing belts; two on each side of the processor – pitch 9.5 mm [0.375 in]
- Belt speed: 2.5 - 35 mm/s
- Processor dimensions in mm (LxWxH): 1210 x 258 x 510
- Shipping dimensions in mm (LxWxH): 1570 x 540 x 770
- Processor weight: 88 Kg [194 lbs]

Product Range/Sizes

- Tubing diameter (max): 19 mm [0.75 in]
- Tubing length (max): Up to 90 mm [3.5 in]



Product Features

- Closed-loop time and temperature control
- Continuous controlled process
- Adaptable for different applications
- Emergency stop-switch
- Slim-profile benchtop design

Easy Operation

The XB-17 belt heater is a more reliable, safer and faster alternative to heat guns for heat shrink wire processing applications. This compact, conveyor-style machine provides a controlled process for a wide variety of heat-shrinkable tubing products. Double-sided timing belts on the top and bottom of the processing chamber draw the assemblies through a thermally controlled infrared heat zone and through a fan-cooled zone before depositing them safely into an unloading bin.

Labor costs are reduced significantly because once an assembly is loaded, the operator can begin preparing another assembly. The throughput rate is usually limited by the rate at which the operator can load assemblies into the processor.

Controlled Heating Zone

The XB-17 processor has two stamped foil heating elements that are manufactured to a strict wattage specification. Consistent temperatures (maximum working temperature setting is 600° C) are controlled by a thermocouple embedded into the upper heating element connected to a closed-loop temperature controller. Plus, conveyor belts reverse direction to prevent product from entering the heating chamber if the system is outside the desired temperature settings.

Advanced Connectivity

An integrated multi-language touchscreen interface with programmable logic system can adjust belt speed, temperature settings, and offers users the ability to create hundreds of unique profiles.

Connection ports on the XB-17 support several options such as a barcode scanner, automatic temperature calibration, and remote access to an upstream welder.

Versatile Design

The processor is designed to process a broad range of heat-shrinkable products up to 19 mm [0.75 in] in diameter and 90 mm [3.5 in] in length. The infrared energy source is well-suited to efficient processing of either single-wall or adhesive-lined tubing. Heat output can be controlled to accommodate a wide variety of products and substrates.

MACHINE ORDERING INFORMATION

Description	PN
XB-17, 220V	2375310-1
XB-17, 110V	2375310-2

XB-19 BELT HEATER

Technical Data

- Electrical supply: **[PN 2375320-X]** 220 VAC, 1Ø
- Heating elements: 2 ea; standard length (100 mm) **[PN 2375320-1]**; wide length (160 mm) **[PN 2375320-2]**
- Maximum temperature setting: 600° C
- Belt speed: 2.5 - 35 mm/s
- Processor dimensions in mm (LxWxH): 1340 x 260 x 550
- Weight: 92 kg [203 lbs]

Product Range/Sizes

- Tubing diameter (max): 25 mm
- Tubing length 100 mm **[PN 2375320-1]**; 160 mm **[PN 2375320-2]**

Product Features

- Adjustable belt distance to accommodate larger tubing lengths
- Closed-loop time and temperature control
- Continuous controlled process
- Adaptable for different applications
- Emergency stop-switch
- Slim-profile bench-top design

Easy Capacity

The XB-19 machine is a continuous-running process belt heater suitable for handling a wide range of workpieces and substrates including RAYCHEM tubing products for ring and FASTON terminals.

An adjustable belt distance feature allows operators to extend the processing range of tubing products from 100 mm up to 160 mm.

Excellent Process Control

The system provides superior heat shrink management with both the motor speed and heating elements having closed-loop control.

Two pairs of timing belts grip the individual workpieces and carry them through an infrared heating zone. The workpieces then pass through a cooling zone before finally being deposited into a collection bin.

For added safety, conveyor belts reverse direction to prevent product from entering the heating chamber if the system is outside the desired temperature settings.


Advanced Connectivity

An integrated multi-language touchscreen interface with programmable logic system can adjust belt speed, temperature settings, and offers users the ability to create hundreds of unique profiles.

Connection ports on the XB-19 support several options such as a bar-code scanner, automatic temperature calibration, and remote access to an upstream welder.

Versatile Design

The processor is designed to process a broad range of heat-shrinkable products up to 25 mm in diameter and 160 mm in length. Its infrared energy source is well-suited to efficient processing of either single-wall or adhesive-lined tubing. Heat output can be controlled to accommodate a wide variety of products and substrates.



HEAT SHRINK MACHINES

FOR RAYCHEM HEAT SHRINK PRODUCTS FROM TE CONNECTIVITY

MACHINE ORDERING INFORMATION

Description	PN
XB-19, Standard (100 mm)	2375320-1
XB-19, Wide (160 mm)	2375320-2

PRODUCT HOLDERS

Please consult TE sales for the correct part numbers for your application.

Extra Accessories for the XB-17 & XB-19 Line

XB-17 and XB-19 belt heaters include a host of options to increase accuracy, performance and flexibility. Both models can be sold with field-installed, or factory-mounted automatic centering devices. Additional options include custom Manufacturing Execution Systems (MES), wheeled carts, and custom product holders for ring terminal and stub splice applications.



PLUG-AND-PLAY CENTERING DEVICE

XB-17 & XB-19 Automatic Centering Device

For improved accuracy, XB-17 & XB-19 model belt heaters can be equipped with an easy-to-install automatic centering device.

XB BELT HEATER OPTIONS & ACCESSORIES

Description	PN
XB-17 & XB-19 Automatic Centering Device	2375330-1
XB-17 / XB-19 Machine Stand	2375329-1
XB-17 Upper Heating Element (220V)	2375317-3
XB-17 Lower Heating Element (220V)	2375317-4
XB-17 Upper Heating Element (110V)	2375317-5
XB-17 Lower Heating Element (110V)	2375317-6
XB-19 Upper Heating Element (100 mm width)	2375327-3
XB-19 Lower Heating Element (100 mm width)	2375327-4
XB-19 Upper Heating Element (160 mm width)	2375327-5
XB-19 Lower Heating Element (160 mm width)	2375327-6

XS-D1 SHUTTLE MACHINE

Technical Data

- Electrical supply: 230 V single phase
- Power consumption: Max. 3520 W
- Maximum temperature setting: 550° C (recommended 500° C)
- Process rate: 120/hour maximum depending on application and operator
- Heating times: 3 to 99 sec. depending on application
- Weight: 170Kg
- Dimensions – (L x H x D): 1350 x 700 x 650 mm
- Product range: Wide range of RAYCHEM tubing products such as all dual wall tubes, single wall tubes and ES-Caps (maximum diameter 70 mm [2.76 in], and maximum length 100 mm [3.94 in] in-line / 250 mm [9.84 in] end)



Product Features

- Automatic cycle start once heater is automatically positioned over product, which gives improved process control (recommended for adhesive lined heat shrinkable tubing e.g. sealing applications)
- Automatic heating head retraction at end of heating & cooling cycle helps prevent damage to components
- Multiple product fixture assemblies give increased process rates
- Automatic movement of the heaters and door opening once process is finished
- Optional quick fixture replacement
- Fixture recognition for correct product processing

Applications

The XS-D1 is suitable for the installation of a range of RAYCHEM, heat shrinkable tubing products onto a variety of small components, e.g. ring terminals, FASTON terminals and small connectors as well as in-line products. The machine is provided with two workstations and a movable heating head.

Each workstation provides fixtures for common products, but these can be replaced by customized ones which can be specified and ordered separately. These support the workpieces and locate the tubing products. The operator loads the workpieces into the fixtures at one of the workstations, confirms that the tubing product is correctly positioned and then closes the cover, then the heat head automatically positions to start the heating cycle. The operator then continues with loading/unloading the other workstation while the heating/cooling cycle is taking place.

The XS-D1 shuttle is provided with closed loop temperature control, ensuring repeatability during production, and a calibration is also possible ensuring temperature is consistent.

Once the other workstation has been loaded and the first installation is complete, the heat head is moved into position over the product and the next heating cycle initiated. Heating times vary typically from 3 to 30 seconds depending on the size and type of tubing product. Process rates up to 120 pieces/hour can be achieved depending on the heating time and the time taken by the operator to load/unload the workpieces. Cooling time can also be programmed to handle safely products once process is finished.

The installation temperature/power can be varied according to product type/size and required cycle times.

The heating elements, which are continuously energized, are infrared medium wavelength and consists of a coiled resistance wire contained in quartz glass plates. The closed loop temperature control uses similar elements but has integral thermocouple sensor.

ORDERING INFORMATION

Description	PN
XS-D1 Standard	2410400-1
XS-D1 Plus	2410400-2

The XS-D1 shuttle machine is also available with customized fixtures. Ordering information is available upon request.

MODEL 105 TUNNEL OVEN

Technical Data

- Electrical supply: 210 – 240 VAC, 20 A, 50/60 Hz
- Heating elements: (2) 1500 W infrared stamped foil with black quartz face
- Drive system: DC gear motor with closed loop motor controller, 3-digit thumb-wheel
- Air flow (cooling): 4 – 100 CFM fans, 2 – for upper heater housing, 2 – for product cooling
- Maximum temperature setting: 600° C
- Conveyor belt system: Wire mesh 70% open
- Belt speed: 6.1 – 152 cm [0.2 – 5.0 ft] per minute
- Processor dimensions (L x W x H): 99 x 68.5 x 41.7 mm
- Control box dimensions (L x W x H): 51.5 x 21.0 x 17.8 cm
- Control box weight: 7.7 kg (17 lbs)
- Shipping dimensions (L x W x H): 134.6 x 116.8 x 63.5 cm
- Shipping weight: 146 kg [320 lbs]
- Tubing diameter (max): 98 mm [3.86 in]
- Tubing length (max): 356 mm [14 in] perpendicular to belt travel, unlimited length parallel to belt travel



Product Features

- Closed-loop speed and temperature control
- Continuous controlled process
- Adaptable for different applications
- Heater operation and over-temperature alarm lights
- CE approved

Ordering Information

- Model 105 Tunnel Oven CLTEQ-M105-TUNNEL-OVEN, [PN: 955018-000] (Custom variations available upon request)

Applications

The Model 105 tunnel oven is a reliable and versatile process heater which provides a controlled process for a wide variety of heat shrinkable products.

It is designed as an integrated modular unit. Assemblies are placed on the entry section of a mesh conveyor belt, transported through the heating chamber, across a bank of cooling fans then discharged from the rear of the conveyor.

The upper chamber is cantilevered to permit processing of assemblies that require only a portion of the assembly to pass through the heat zone and is equipped with adjustable heat shields to maximize the oven heating efficiency for various applications.

Controlled Heating Zone

Two stamped foil heating elements provide consistent temperatures (ambient to 600° C) and are controlled by a thermocouple embedded into the upper heating element connected to a closed-loop temperature controller. An alarm light illuminates whenever the actual heating element temperature varies from the set point temperature.

Conveyor Speed Control

The conveyor speed is precisely set by a 3-digit drive controller. The DC drive motor provides constant conveyor speed at any potentiometer setting from 100 to 999 mm [0.2 to 5.0 ft] per minute, for precise heating of assemblies.

HEAT SHRINK MACHINES

FOR RAYCHEM HEAT SHRINK PRODUCTS FROM TE CONNECTIVITY

Minimal Skill Requirements

The open loading area of the entry section requires that the operator simply place an assembly on the mesh conveyor belt within the effective width of the heat zone and collect it at the opposite end.

Versatility

The processor is designed to process a broad range of heat shrinkable products up to 76.2 mm in diameter and infinite length. The infrared energy source is for efficient processing of either single-wall or adhesive-lined tubing. Heat output and drive speed can be controlled to accommodate a wide variety of products and substrates such as HFT 5000, AP-2000, QSZH 125 and other RAYCHEM tubing products.

MACHINE ORDERING INFORMATION

Description	PN
Model 105 Tunnel Oven, Standard	955018-000

AD-3050 SEAL TEST EQUIPMENT

Ordering Information

- AD-3050-SEAL-TEST-EQ-NC PN: **C82893-000**
- Version with integrated timer: AD-3050-SEAL-TEST-EQ-NC-TIMER
PN: **528024-1** (Timer retrofit kit available)

Product Features

- Fast determination of sealing integrity
- Multiple test fixtures
- Easy load and release of test samples
- Connector seal test port
- Timer adjustable from 8 - 120 seconds (only with integrated AD-3050 Seal Test Equipment timer version)



Technical Data

- Pneumatic supply: 600 kPa / 6 bar maximum, filtered supply 200 kPa / 2 bar test pressure maximum (Test pressure typically 50 kPa / 0.5 bar)
- Machine cycle times for seal testing: Typically 1 min.
- Total system noise: Negligible noise from air test
- Dimensions: 550 x 350 x 215 mm (21.7 x 13.8 x 8.5 in) (excludes packing case)
- Weight: 4 Kg (excludes packing case)

MACHINE ORDERING INFORMATION

Description	PN
AD-3050 Seal Tester	C82893-000
AD-3050 Seal Tester with Timer	528024-1

ACCESSORIES ORDERING INFORMATION

Description	PN
AD-3050 Seal Kit, 8 Positions	299155-000
Timer Retrofit Kit	4-529533-7

This kit converts C82893-000 seal tester to 528024-1

HEAT SHRINK MACHINES

FOR RAYCHEM HEAT SHRINK PRODUCTS FROM TE CONNECTIVITY

The AD-3050 is a manually operated pneumatic device, intended for use as a convenient “in process” sampling technique for checking sealed splices.

Different combinations of in-line, end-/stub-splices and various ring terminal applications can be pressure tested in any of the combination of fixtures (8 in total).

There is also a facility to allow leak testing of various connectors. The tool is also intended for use as a quick and easy sampling technique for the preliminary selection of installation conditions where RAYCHEM splice protection products are used.

TE has seen good correlation between results obtained with the AD-3050 seal test and those obtained through water immersion testing. However testing in accordance with the Original Equipment Manufacturer (OEM) specification is the only way of confirming that the OEM specification is being met.

The splice products are located in clamps which deliver the test pressure. The product is immersed in water and pressure is delivered through the wire(s) to the sealed area.

The test result is determined visually by looking for bubbles in the area of the sealing product. Connectors can also be pressure tested by adapting the separate supply fixture to any connector type. Use of this equipment is described in TE's customer manual. This equipment can also check for instances where individual wire strands poke through the installed heat shrinkable sleeve.

FIELD SERVICE SUPPORT

SERVICES

Standard Service

Includes troubleshooting and making repairs

Equipment Installation

Providing installation, set-up and training at time of equipment delivery

Training

- Basic crimp theory
- Hand tool, applicator and equipment set-up, operation and maintenance

Preventive Maintenance and/or Inspection Certification

Provides service for periodic visits to perform preventive maintenance and/or inspection certification service on hand tools, applicators and bench equipment. Inspection of the finished product is made to confirm it meets TE application specifications. Documentation is available upon request for traceability to support your facilities' quality system requirements.



Heat Shrink Machine Selection Guide Based on Tubing Dimensions




■ RBK X1 Processor


■ XB-17 Belt Heater



■ XB-19 Belt Heater Standard


■ XB-19 Belt Heater Wide


■ XS-D1


■ Model 105

Tube length	0...65mm (Standard) 0...75mm (Type 4 heater)	0...90mm	0...100mm	0...160mm	0...100mm (In-line) 0...250mm (End & Ring)	Unlimited length (width: 356mm)
Tube diameter	0...19mm	0...19mm	0...25mm	0...25mm	0...60mm	0...96mm



Sealing Matrix

Application	Products								
	QSZH	RBK-ILS	RBK-VWS	ES-CAP	SCT	RBK-RTP	HTAT	RBK-105-KIT	RBK-85-KIT
Splice Sealing - Inline	✓	✓	✓		✓				
Splice Sealing - Stub				✓					
Ring Terminal Sealing	✓	✓	✓		✓	✓			
Connector Sealing					✓		✓		
Bundle Wire Sealing								✓	✓

[Click here for more information about tubing](#)

Connect With Us

We make it easy to connect with our experts and are ready to provide all the support you need. Visit **tooling.te.com** to chat with a Product Information Specialist.

te.com

TE, TE Connectivity, TE connectivity (logo), and EVERY CONNECTION COUNTS, FASTON, RBK and RAYCHEM are trademarks owned or licensed by the TE Connectivity Ltd. family of companies. Other product names, logos, and company names mentioned herein may be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2024 TE Connectivity. All Rights Reserved.

(Published) 05-24

Contact us today to learn more

E-mail (Americas): toolsales@te.com

Phone (Americas): 800-722-1111 or
717-986-3434

Phone (EMEA): +49-6251-133-3936

Phone (APAC): +86 21 3325 9030

For field service inquiries go to
www.te.com/fieldservice