




Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Receptacle**

Connector System: **Board-to-Board**

Number of Positions: **8**

Number of Rows: **2**

Centerline (Pitch): **2.54 mm [.1 in]**

Features

Product Type Features

Applied Pressure	Standard
PCB Connector Type	PCB Mount Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Stackable	Yes
Number of Positions	8
Number of Rows	2
PCB Mount Orientation	Vertical
Board-to-Board Configuration	Parallel

Electrical Characteristics

Operating Voltage	333 VAC
Insulation Resistance	5000 MΩ

Body Features

Connector Profile	Standard
Primary Product Color	Black



Contact Features

Contact Underplating Material	Nickel
Contact Underplating Material Thickness	1.27 µm[50 µin]
PCB Contact Termination Area Plating Material Finish	Matte
Mating Square Post Dimension	.64 mm[.025 in]
PCB Contact Termination Area Plating Material Thickness	3.81 – 7.62 µm[150 – 300 µin]
Contact Shape & Form	Square
Contact Protection Type	Closed Entry Housing
Contact Base Material	Phosphor Bronze
PCB Contact Termination Area Plating Material	Tin-Lead
Contact Mating Area Plating Material Thickness	.762 µm[30 µin]
Contact Mating Area Plating Material	Gold (Au)
Contact Type	Socket
Contact Current Rating (Max)	2 A

Termination Features

Rectangular Termination Post & Tail Width	.69 mm[.027 in]
Rectangular Termination Post & Tail Thickness	.2 mm[.008 in]
Termination Post & Tail Length	2.92 mm[.115 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Connector Mounting Type	Board Mount
Mating Alignment	Without
PCB Mount Alignment	Without
PCB Mount Retention	Without

Housing Features

Mating Entry Location	Top
Centerline (Pitch)	2.54 mm[.1 in]
Housing Material	Polyester GF

Dimensions

Connector Height	5.03 mm[.198 in]
Row-to-Row Spacing	2.54 mm[.1 in]
Stack Height	10.92 mm[.43 in]



PCB Thickness (Recommended)	1.57 mm[.055 – .094 in]
-----------------------------	-------------------------

Usage Conditions

Housing Temperature Rating	Standard
Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]

Operation/Application

Solder Process Feature	Board Standoff
Circuit Application	Signal

Industry Standards

Compatible With Approved Standards Products	CSA LR7189, UL E28476
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	56
Packaging Method	Box, Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 240°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 5-146257-4 08 MODII HDR DRST B/A .100CL L	 TE Part # 5-103164-2 08 MODII HDR DRRA 3/4SHRD LF	 TE Part # 103166-2 08 MODII HDR DRRA SHRD .100CL	 TE Part # 5-146131-3 08 MODII HDR DRST SFMNT B/A LF
 TE Part # 5-146130-3 08 MODII HDR DRST SFMNT B/A LF	 TE Part # 5-146253-4 08 MODII HDR DRST B/A .100CL LF	 TE Part # 5-102617-2 08 MODII HDR DRRA SHRD LF	 TE Part # 5-103166-2 08 MODII HDR DRRA SHRD LF
 TE Part # 5-103326-4 08 MODII HDR DRRA B/A .100CL	 TE Part # 86286-1 KEYING PLUG		

Also in the Series | Modu Connector System

 Board-to-Board Headers & Receptacles(240)	 Board-to-Board Jumpers & Shunts(5)	 Connector Hardware(3)	 PCB Headers & Receptacles(240)
---	--	---------------------------	------------------------------------

Customers Also Bought



TE Part #T4171320008-001
M12,FRONT MOUNT,FEMALE, A, 8P,
0.2M WIRE

TE Part #5-87589-2
12 MODII HDR DRST SHRD .100CL

TE Part #8-87589-5
08 MODII HDR DRST SHRD .100CL

TE Part #87631-3
08 MODIV HSG COMP DR .100 POL

TE Part #87631-7
12 MODIV HSG COMP DR .100 POL

TE Part #87809-2
MOD V RECP PLTD SN

TE Part #5-146763-6
04 MODII VRT SR CE 100

TE Part #3-1437652-9
6PCV-02-006=6PCV ASSEMBLY

TE Part #5-1437652-4
6PCV-03-006=6PCV ASSEMBLY

TE Part #2-2176513-9
CJP 1000W 470R 5% Lead

Documents

Product Drawings

08 MODII VRT DR CE 100/115

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-534206-4_N.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5-534206-4_N.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-534206-4_N.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



AMPMODU_INTERCONNECTION_SYSTEM_SECTION5

English

Product Specifications

Application Specification

English