



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Receptacle**

Connector System: **Board-to-Board**

Number of Positions: **14**

Number of Rows: **2**

Centerline (Pitch): **2.54 mm [.1 in]**

Features

Product Type Features

Applied Pressure	Standard
PCB Connector Type	PCB Mount Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Stackable	Yes
Number of Positions	14
Number of Rows	2
PCB Mount Orientation	Vertical
Board-to-Board Configuration	Parallel

Electrical Characteristics

Operating Voltage	333 VAC
Insulation Resistance	5000 MΩ

Body Features

Connector Profile	Standard
Primary Product Color	Black



Contact Features

	150 µin
Mating Square Post Dimension	.64 mm[.025 in]
Contact Shape & Form	Square
Contact Protection Type	Closed Entry Housing
Contact Base Material	Phosphor Bronze
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	.762 µm[30 µin]
Contact Mating Area Plating Material	Gold (Au)
Contact Type	Socket
Contact Current Rating (Max)	2 A

Termination Features

Rectangular Termination Post & Tail Width	.69 mm[.027 in]
Rectangular Termination Post & Tail Thickness	.2 mm[.008 in]
Termination Post & Tail Length	2.92 mm[.115 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Connector Mounting Type	Board Mount
Mating Alignment	Without
PCB Mount Alignment	Without
PCB Mount Retention	Without

Housing Features

Mating Entry Location	Top
Centerline (Pitch)	2.54 mm[.1 in]
Housing Material	Polyester GF

Dimensions

Connector Height	5.03 mm[.198 in]
Row-to-Row Spacing	2.54 mm[.1 in]
Stack Height	10.92 mm[.43 in]
PCB Thickness (Recommended)	1.57 mm[.055 – .094 in]

Usage Conditions

Housing Temperature Rating	Standard
----------------------------	----------



Operating Temperature Range

-65 – 105 °C[-85 – 221 °F]

Operation/Application

Solder Process Feature	Board Standoff
Circuit Application	Signal

Industry Standards

Compatible With Approved Standards Products	CSA LR7189, UL E28476
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	32
Packaging Method	Box, Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 240°C


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts




TE Part # 5-146269-7
14 MODII HDR DRST B/A 100 W/HD



TE Part # 5-103326-7
14 MODII HDR DRRA B/A .100CL



TE Part # 5-103166-5
14 MODII HDR DRRA SHRD LF



TE Part # 5-146257-7
14 MODII HDR DRST B/A .100CL L




TE Part # 5-146253-7
14 MODII HDR DRST B/A .100CL LF



TE Part # 86286-1
KEYING PLUG



TE Part # 5-146261-7
14 MODII HDR DRST B/A .100CL LF




TE Part # 5-103164-5
14 MODII HDR DRRA 3/4SHRD LF



TE Part # 103166-5
14 MODII HDR DRRA SHRD .100CL



TE Part # 5-146130-6
14 MODII HDR DRST SFMNT B/A LF




TE Part # 5-146131-6
14 MODII HDR DRST SFMNT B/A LF




TE Part # 5-102617-5
14 MODII HDR DRRA SHRD LF

Also in the Series | [Modu Connector System](#)




Board-to-Board Headers & Receptacles(240)



Board-to-Board Jumpers & Shunts(5)




Connector Hardware(3)




PCB Headers & Receptacles(240)

Customers Also Bought



TE Part #1SNG607002R0000
EP-LN-M12-GR-A



TE Part #G-NICO-023
0.1 DEG C ACCURACY QFN TEMP SENSOR




TE Part #RXM-GPS-RM-T
Module RM L1 GPS RX RCVR T&R



TE Part #10220685-00
CHPG-100K +/- 2% B 4075 +/- 1% BT63-H







TE Part #5-102920-2
MOD IV RECP LP LF




TE Part #1644055-1
UNIV MATE-N-LOK HOUSING 6W



TE Part #2-2176398-3
3502 110K 1%



TE Part #4-2328724-5
45PIN 0.3MMP FPC CONNECTOR,
FRONT FLIP



TE Part #5558503-1
MJ ASSY,4P,8 POS,CAT 5E,PCB GND

TE Part #GA23K3CG595
CHPC-TAIWAN GOLD CHIP

Documents

Product Drawings

14 MODII VRT DR CE 100/115

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-534206-7_N.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5-534206-7_N.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-534206-7_N.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

AMPMODU_INTERCONNECTION_SYSTEM_SECTION5

English

Product Specifications

Application Specification

English